

**OXYGEN- oxygen gas**  
**Superior Welding Supply Co**

-----  
**HIGH PRESSURE OXYGEN LABEL**

OXYGEN, COMPRESSED USP  
UN1072

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

SUPERIOR WELDING SUPPLY CO.  
900 COMMERCIAL ST. WATERLOO, IA 50702  
319-232-6861  
CONTENTS: LTRS  
CU. FT.



OXYGEN, REFRIGERATED LIQUID USP

UN1073

CONTENTS: LTRS:

CU FT:

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act. Produced by Air Liquefaction.

Produced by Air Liquefaction.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

**FIRST AID:** IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.


CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

SUPERIOR WELDING SUPPLY CO.  
 900 COMMERCIAL ST. WATERLOO, IA 50702  
 319-232-6861

**REFRIGERATED LIQUID**

**OXYGEN,  
 REFRIGERATED  
 LIQUID  
 USP  
 UN1073**



CONTENTS: LTRS   
 CU FT

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **do not**. Unintended use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act. Produced by Air Liquide.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE. OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection, in case of fire. Stop work if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Check valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

**FIRST AID: IF ON SKIN:** Thaw frostbitten parts with lukewarm water. Do not rub affected area. Get immediate medical attention/attention. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

SUPERIOR WELDING SUPPLY CO.  
 900 COMMERCIAL ST. • WATERLOO, IA 50702  
 319-232-6861

47136  
 (01/15)

## OXYGEN

oxygen gas

### Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:49653-003
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
<b>OXYGEN</b> (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

### Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:49653-003-01	200 L in 1 CYLINDER; Type 0: Not a Combination Product	03/21/1980	
2	NDC:49653-003-02	340 L in 1 CYLINDER; Type 0: Not a Combination Product	03/21/1980	
3	NDC:49653-003-03	400 L in 1 PACKAGE; Type 0: Not a Combination Product	03/21/1980	
4	NDC:49653-003-04	636 L in 1 CYLINDER; Type 0: Not a Combination Product	03/21/1980	

5	NDC:49653-003-05	660 L in 1 CYLINDER; Type 0: Not a Combination Product	03/21/1980	
6	NDC:49653-003-06	3240 L in 1 CYLINDER; Type 0: Not a Combination Product	03/21/1980	
7	NDC:49653-003-07	7100 L in 1 CYLINDER; Type 0: Not a Combination Product	03/21/1980	
8	NDC:49653-003-08	127305 L in 1 CONTAINER; Type 0: Not a Combination Product	03/21/1980	

## Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	03/21/1980	

**Labeler** - Superior Welding Supply Co (022367387)

## Establishment

Name	Address	ID/FEI	Business Operations
Superior Welding Supply Co		022367387	manufacture(49653-003)

Revised: 10/2023

Superior Welding Supply Co