NITROUS OXIDE- nitrous oxide gas
Fullerton Welding Supply

Nitrous Oxide

Principal for Nitrous Oxide Product

Use only with equipment cleaned for oxygen service and rated for cylinder pressure.
Use a back flow preventative device in the piping.
Close valve after each use and when empty. Cylinder temperature should not exceed 52˚C (125˚F)
Use in accordance with Material Safety Data Sheet (MSDS).
DO NOT REMOVE THIS PRODUCT LABEL.
⚠ **WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

FWS10

☐ _____   ☐ **50 LB**
☐ **ANE**   ☐ **56 LB**   H

NITROUS OXIDE

nitrous oxide gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:42751-1070
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
NITROUS OXIDE (UNII: K50XQU1029) (NITROUS OXIDE - UNII:K50XQU1029)	NITROUS OXIDE	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:42751-1070-1	19.85 L in 1 CYLINDER		
2	NDC:42751-1070-2	21.84 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		02/06/2008	

Labeler - Fullerton Welding Supply (556832384)

Establishment

Name	Address	ID/FEI	Business Operations

Fullerton Welding Supply		556832384	manufacture(42751-1070)