

OXYGEN - oxygen gas
Buffalo Welding Corp

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

OXYGEN COMPRESSED LABEL

OXYGEN COMPRESSED USP UN 1072 OXYGEN-2 PRODUCED BY AIR LIQUEFACTION. CAS 7782-44-7 18033 (R 04/05)

WARNING: HIGH PRESSURE GAS VIGOROUSLY ACCELERATES COMBUSTION.



OXYGEN COMPRESSED LABEL


OXYGEN COMPRESSED U.S.P. UN 1072 OXYGEN-2 PRODUCED BY AIR LIQUEFACTION

LOT NO _____ EXP DATE _____ LITERS _____ PRESSURE _____ (PSIG AT 70F)

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE

**OXYGEN,
COMPRESSED
U.S.P.
UN 1072**



PRODUCED BY AIR LIQUEFACTION

Lot No. _____ Exp. Date _____
Liters _____ Pressure _____ (PSIG @ 70 F)

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.**

CAUTION: Federal law prohibits dispensing without prescription.

Uninterrupted use of high concentrations of oxygen over a long duration without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Container temperature should not exceed 52°C (125°F). Close valves after each use and when empty. Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

DO NOT REMOVE THIS PRODUCT LABEL.

REFRIGERATED LIQUID LABEL

OXYGEN COMPRESSED U.S.P. UN 1072 OXYGEN-2 PRODUCED BY AIR LIQUEFACTION

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT FORCE FIT OR CHANGE CONNECTIONS


WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE

41533 (R 10/04) CAS 7782-44-7

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP**

UN1073



↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑
DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.
 Use only with equipment cleaned for oxygen service.
 Store and use with adequate ventilation.
 Do not get liquid in eyes, on skin, or clothing.
 For liquid withdrawal, wear face shield and gloves.
 Do not drop. Use suitable hand truck for container movement.
 Avoid spills. Do not walk on or roll equipment over spills.
 Cylinder temperature should not exceed 52°C (125°F).
 Close valve after each use and when empty.
 Use a back flow preventive device in the piping.
 Use in accordance with the **Material Safety Data Sheet (MSDS)**.

FIRST AID: **IN CASE OF FROSTBITE**, obtain medical treatment immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

41533
(R 10/04)

PRODUCT WARNINGS AND PRECAUTIONS

FOR EMERGENCY USE ONLY WHEN ADMINISTERED BY PROPERLY TRAINED PERSONNEL FOR OXYGEN DEFICIENCY AND RESUSCITATION. FOR ALL OTHER MEDICAL APPLICATIONS **Rx ONLY**. FEDERAL LAW PROHIBITS DISPENSING WITHOUT A PRESCRIPTION. UNINTERRUPTED USE OF HIGH CONCENTRATIONS OF OXYGEN OVER A

LONG DURATION WITHOUT MONITORING ITS EFFECT ON OXYGEN CONTENT OF ARTERIAL BLOOD MAY BE HARMFUL. USE ONLY WITH PRESSURE REDUCING EQUIPMENT AND APPARATUS FOR OXYGEN. DO NOT ATTEMPT TO USE ON PATIENTS WHO HAVE STOPPED BREATHING UNLESS USED IN CONJUNCTION WITH RESUSCITATIVE EQUIPMENT. PRODUCED BY AIR LIQUEFACTION.

WARNING: KEEP OIL GREASE AND COMBUSTIBLES AWAY. USE ONLY WITH EQUIPMENT CLEANED FOR OXYGEN SERVICE. STORE AND USE WITH ADEQUATE VENTILATION. DO NOT GET LIQUID IN EYES ON SKIN OR CLOTHING. FOR LIQUID WITHDRAWAL WEAR FACE SHIELD AND GLOVES. DO NOT DROP. USE SUITABLE HAND TRUCK FOR CONTAINER MOVEMENT. AVOID SPILLS. DO NOT WALK ON OR ROLL EQUIPMENT OVER SPILLS. CONTAINER TEMPERATURE SHOULD NOT EXCEED 52 c (125 f) CLOSE VALVE AFTER EACH USE AND WHEN EMPTY. USE IN ACCORDANCE WITH MATERIAL SAFETY DATA SHEET (MSDS)

FIRST AID: IN CASE OF FROSTBITE OBTAIN MEDICAL TREATMENT IMMEDIATELY. DO NOT REMOVE THIS PRODUCT LABEL.

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:25336-5563
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:25336-5563-1	139 L in 1 CYLINDER		
2	NDC:25336-5563-2	424 L in 1 CYLINDER		
3	NDC:25336-5563-3	671 L in 1 CYLINDER		
4	NDC:25336-5563-6	8694 L in 1 CYLINDER		
5	NDC:25336-5563-4	3540 L in 1 CYLINDER		
6	NDC:25336-5563-5	7108 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		01/01/1969	

Labeler - Buffalo Welding Corp (013708425)

Registrant - Buffalo Welding Corp (013708425)

Establishment

Name	Address	ID/FEI	Business Operations
Buffalo Welding Corp		013708425	manufacture

Revised: 1/2010

Buffalo Welding Corp