


OXYGEN- oxygen gas
Jackson Welding Supply Co Inc.

oxygen

OXYGEN, COMPRESSED USP UN1072 PRODUCED BY AIR LIQUEFACTION OXYGEN 2
WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical application, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

JACKSON WELDING & GAS PRODUCTS 4 PIXLEY INDUSTRIAL PKWY ROCHESTER, NY 14624 . 585-235-2920



OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2

CONTENTS: LTRS: CU FT:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this

container be filled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills, Do not walk on or fall equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.


CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

JACKSON WELDING & GAS PRODUCTS 4 PIXLEY INDUSTRIAL PKWY ROCHESTER, NY

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP**

UN1073




LTRS:
CU FT:

CONTENTS: _____

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal *Food, Drug, and Cosmetic Act*.
Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.
CAS: 7782-44-7



DO NOT REMOVE THIS PRODUCT LABEL

JACKSON WELDING & GAS PRODUCTS
4 PIXLEY INDUSTRIAL PKWY
ROCHESTER, NY 14624 • 585-235-2920

47136
(01/15)

14624 . 585-235-2920

OXYGEN

oxygen gas

Product Information

Product Type

HUMAN PRESCRIPTION DRUG

Item Code (Source)

NDC:42068-001

Route of Administration RESPIRATORY (INHALATION)

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:42068-001-01	425 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
2	NDC:42068-001-02	623 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
3	NDC:42068-001-03	680 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
4	NDC:42068-001-04	4361 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	
5	NDC:42068-001-05	7079 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1973	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	01/01/1973	

Labeler - Jackson Welding Supply Co Inc. (013113287)

Establishment

Name	Address	ID/FEI	Business Operations
Jackson Welding Supply Co Inc.		013113287	manufacture(42068-001)

Revised: 10/2023

Jackson Welding Supply Co Inc.