


OXYGEN- oxygen gas
Medwiser, Inc.

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

Oxygen, USP

Principal for Oxygen Product

**OXYGEN,
REFRIGERATED
LIQUID USP**
UN 1073



CONTENTS: _____ LITERS

CAS NO: 7782-44-7

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID:

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

©Applied Home Healthcare Equipment 2014

Representative Labeling
pursuant to 21 CFR 207.3 (10)
Company name and contact information are
printed in this area

OXYGEN,

REFRIGERATED

LIQUID USP

UN 1073

CONTENTS _____ LITERS

CAS NO: 7782-44-7

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS

REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR

INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON
IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood.

Keep and store away from clothing and other combustible materials.

Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID:

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

DO NOT REMOVE THIS PRODUCT LABEL.

Warning: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**OXYGEN,
COMPRESSED USP**
UN 1072



DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

CAS NO: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. ©Applied Home Healthcare Equipment 2014

Contents	Size
113 Liters	<input type="checkbox"/> M4
165 Liters	<input type="checkbox"/> M6
255 Liters	<input type="checkbox"/> C
425 Liters	<input type="checkbox"/> D
680 Liters	<input type="checkbox"/> E
7080 Liters	<input type="checkbox"/> H
____ Liters	<input type="checkbox"/> Other

**Representative Labeling
pursuant to 21 CFR 207.3 (10)
Company name and contact information
are printed in this box**

OXYGEN

COMPRESSED

USP

UN 1072

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use.

CAS NO: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency

and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen

content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.



OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:74301-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:74301-001-01	45 L in 1 DEWAR; Type 0: Not a Combination Product	08/30/2010	
2	NDC:74301-001-02	165 L in 1 CYLINDER; Type 0: Not a Combination Product	08/30/2010	
3	NDC:74301-001-03	680 L in 1 CYLINDER; Type 0: Not a Combination Product	08/30/2010	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		08/30/2010	

Labeler - Medwiser, Inc. (054897984)**Establishment**

Name	Address	ID/FEI	Business Operations
Medwiser, Inc.		054897984	manufacture(74301-001)

Revised: 12/2023

Medwiser, Inc.