

OXYGEN - oxygen gas
Industrial Gas Distributors Inc

Oxygen


OXYGEN, COMPRESSED USP UN1072
PRODUCED BY AIR LIQUEFACTION
OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical application, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

Industrial Gas DISTRIBUTORS 1346 MONAD ROAD BILLINGS, MT 59101 406-256-3344



OXYGEN, COMPRESSED USP UN1072
PRODUCED BY AIR LIQUEFACTION
OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical application, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS GAS UNDER

PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

Industrial Gas DISTRIBUTORS 1346 MONAD ROAD BILLINGS, MT 59101 406-256-3344

OXYGEN, COMPRESSED USP

UN1072



Produced by Air Liquefaction

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal *Food, Drug, and Cosmetic Act*.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (0) before use.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.



1346 MONAD ROAD • BILLINGS, MT 59101
406-256-3344

40035
(01/15)



REFRIGERATED LIQUID OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2
WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of

arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be filled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills, Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

Industrial Gas DISTRIBUTORS 1346 MONAD ROAD BILLINGS, MT 59101 406-256-3344

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP**



UN1073

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **R_x** only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children.

Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the *Federal Food, Drug, and Cosmetic Act*.

Produced by Air Liquefaction

PRODUCED BY AIR LIQUEFACTION.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL



Industrial Gas
DISTRIBUTORS

1346 MONAD ROAD • BILLINGS, MT 59101
406-256-3344

41533
(01/15)

OXYGEN

oxygen gas

Product Information

Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:55749-101
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:55749-101-01	651 L in 1 CYLINDER		
2	NDC:55749-101-02	396 L in 1 CYLINDER		

3	NDC:55749-101-03	651 L in 1 CYLINDER		
4	NDC:55749-101-04	7957 L in 1 CYLINDER		
5	NDC:55749-101-05	113 L in 1 CYLINDER		
6	NDC:55749-101-06	170 L in 1 CYLINDER		
7	NDC:55749-101-07	198 L in 1 CYLINDER		
8	NDC:55749-101-08	227 L in 1 CYLINDER		
9	NDC:55749-101-09	255 L in 1 CYLINDER		
10	NDC:55749-101-10	283 L in 1 CYLINDER		
11	NDC:55749-101-11	3511 L in 1 CYLINDER		
12	NDC:55749-101-12	396 L in 1 CYLINDER		
13	NDC:55749-101-13	680 L in 1 CYLINDER		
14	NDC:55749-101-14	651 L in 1 CYLINDER		
15	NDC:55749-101-15	7051 L in 1 CYLINDER		
16	NDC:55749-101-16	3540 L in 1 CYLINDER		
17	NDC:55749-101-17	2350 L in 1 CYLINDER		
18	NDC:55749-101-18	4361 L in 1 CYLINDER		
19	NDC:55749-101-19	9543 L in 1 CYLINDER		
20	NDC:55749-101-20	160 L in 1 DEWAR		
21	NDC:55749-101-21	180 L in 1 DEWAR		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141358	04/01/1987	

Labeler - Industrial Gas Distributors Inc (796570901)

Establishment

Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		829720098	manufacture

Revised: 12/2015

Industrial Gas Distributors Inc