

OXYGEN - oxygen gas
Northern Welding Supply

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, [click here](#).

Compressed Oxygen Label

OXYGEN, COMPRESSED USP

UN1072

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing. Unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: HIGH PRESSURE OXIDIZING GAS.

VIGOROUSLY ACCELERATES COMBUSTION.

Keep oil and grease away.

Open valve slowly.

Store and use with adequate ventilation.

Use only with equipment cleaned for oxygen service and rated for cylinder pressure.

Use a back flow preventive device in the piping.

Close valve after each use and when empty.

Cylinder temperature should not exceed 52C (125F).

Use in accordance with the

Material Safety Data Sheet (MSDS).

NET CONTENTS

CYLINDER TYPE	LITERS
T	9310
K	6900
S	4250
D, E, Y	3500
Q	2320
XL	1970
AN-E	625
AN-D	360
R	570
AN-C	248
AN-B	164


LOT NUMBER _____

DO NOT REMOVE THIS PRODUCT LABEL

AMERICAN WELDING AND GAS
WAUSAU, WI

**OXYGEN,
COMPRESSED
USP**

UN1072



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other applications, **caution**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction

**WARNING: HIGH PRESSURE OXIDIZING GAS.
VIGOROUSLY ACCELERATES COMBUSTION.**

Keep oil and grease away.

Open valve slowly.

Store and use with adequate ventilation.

Use only with equipment cleaned for oxygen service and rated for cylinder pressure.

Use a back flow preventive device in the piping.

Close valve after each use and when empty.

Cylinder temperature should not exceed 52°C (125°F).

Use in accordance with the **Material Safety Data Sheet (MSDS)**.

NET CONTENTS

CYLINDER TYPE	LITERS
T	9310
K	6900
S	4250
D,E,Y	3500
Q	2320
XL	1970
AH-E	625
AN-D	360
R	570
AN-C	248
AN-B	164

LOT NUMBER _____

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

AMERICAN WELDING AND GAS

WAUSAU, WI

41100 (R07/04)

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:10825-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:10825-001-01	164 L in 1 CYLINDER		
2	NDC:10825-001-02	248 L in 1 CYLINDER		
3	NDC:10825-001-03	360 L in 1 CYLINDER		
4	NDC:10825-001-04	570 L in 1 CYLINDER		
5	NDC:10825-001-05	625 L in 1 CYLINDER		
6	NDC:10825-001-06	1970 L in 1 CYLINDER		
7	NDC:10825-001-07	2320 L in 1 CYLINDER		
8	NDC:10825-001-08	3500 L in 1 CYLINDER		
9	NDC:10825-001-09	4250 L in 1 CYLINDER		
10	NDC:10825-001-10	6900 L in 1 CYLINDER		
11	NDC:10825-001-11	9310 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		01/01/1974	

Labeler - Northern Welding Supply (806534954)

Establishment

Name	Address	ID/FEI	Business Operations
Northern Welding Supply		806534954	manufacture

Revised: 10/2010

Northern Welding Supply