

**OXYGEN- oxygen gas**  
**Jp's Specialty Welding**

*Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, [click here](#).*

-----

**OXYGEN-OXYGEN GAS**  
**JP'S SPECIALTY WELDING, LLC**

**Oxygen**

OXYGEN COMPRESSED USP

UN1072

DO NOT REMOVE THIS PRODUCT LABEL

OXYGEN 2

CONTENTS:LTRS. CUFT

WARNING For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, RXonly. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effects on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced of Air Liquefaction. Warning: HIGH PRESSURE OXIDIZING GAS. VIGEROUSLY ACCELERATED COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventative device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52°C(125°F). Use in accordance with the **Material Safety Data Sheet (MSDS)**.

DO NOT REMOVE PRODUCT LABEL

**OXYGEN  
COMPRESSED  
USP**



17033

(R 0405)

CAS: 7782-44-7

should not exceed 52°C (125°F) Use in accordance with the Material Safety Data Sheet (MSDS)

DO NOT REMOVE THIS PRODUCT LABEL

**J.P. SPECIALTY WELDING & SUPPLY, LLC**  
MANUFACTURED AT:  
2783 N. HWY 1053 • FORT STOCKTON, TX 79735 • 432-339-8056

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, without interruption use of high concentrations of oxygen over a long duration. Use only on monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on equipment. **WARNING:** HIGH PRESSURE. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F) Use in accordance with the Material Safety Data Sheet (MSDS)

**CONTENTS:**

LTRS. ☐  
CU.FT. ☐

# OXYGEN

oxygen gas

## Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:8 1174-560
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

## Active Ingredient/Active Moiety

<b>Ingredient Name</b>	<b>Basis of Strength</b>	<b>Strength</b>
<b>OXYGEN</b> (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

## Packaging

#	<b>Item Code</b>	<b>Package Description</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
1	NDC:8 1174-560-01	400 L in 1 CYLINDER; Type 0: Not a Combination Product	11/04/2003	

## Marketing Information

<b>Marketing Category</b>	<b>Application Number or Monograph Citation</b>	<b>Marketing Start Date</b>	<b>Marketing End Date</b>
unapproved medical gas		11/04/2003	

**Labeler** - Jp's Specialty Welding (795968858)

**Registrant** - Jp's Specialty Welding (795968858)

## Establishment

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
JP's Specialty Welding		795968858	manufacture(8 1174-560)

Revised: 11/2020

Jp's Specialty Welding