

MEDICAL AIR - oxygen gas

Norco, Inc.

MEDICAL AIR USP LABEL AIR COMPRESSED

MEDICAL AIR USP

AIR, COMPRESSED NON-FLAMMABLE GAS 2 41002 (R 08/09)
(19.5%-23% Oxygen, 77%-80.5% Nitrogen)

UN1002

WARNING: For breathing support when used by properly trained personnel. For medical applications, Rx only.

Administration of Medical Air may be hazardous or contraindicated. For use only by or under the supervision

of a licensed practitioner who is experienced in the use and administration of Medical Air and is familiar with

the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards,

contraindications, and side effects and the precautions to be taken.

Lot No. Cyl. Size Contents CF

T 310 ft³

K 230 ft³

E 23 ft³

WARNING: HIGH PRESSURE GAS. MAY ACCELERATE COMBUSTION.

Keep oil and grease away. Use equipment rated for cylinder pressure. Cylinder temperature should not exceed

52 degrees C (125 degrees F). Close valve after each use and when empty. Use a back flow preventive device in

the piping. Use in accordance with the **Material Safety Data Sheet (MSDS)**.

CAS: OXYGEN 7782-44-7 NITROGEN: 7727-37-9

DO NOT REMOVE THIS PRODUCT LABEL


NORCO, INC. 898 W. Gowen Rd Boise, ID 83705 208-336-1643

USPUN1002

MEDICAL AIR USP

AIR, COMPRESSED

(19.5%- 23% Oxygen,
77% - 80.5% Nitrogen)



UN1002

WARNING:For breathing support when used by properly trained personnel. For medical applications, **Rx only**.

Administration of Medical Air may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Medical Air and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken.

Lot No.	Cyl. Size	Contents CF
	T	310 ft ³
	K	230 ft ³
	E	23 ft ³

WARNING:HIGH PRESSURE GAS. MAY ACCELERATE COMBUSTION.

Keep oil and grease away. Use equipment rated for cylinder pressure. Cylinder temperature should not exceed 52°C (125°F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the **Material Safety Data Sheet (MSDS)**.

CAS: OXYGEN 7782-44-7 NITROGEN: 7727-37-9

DO NOT REMOVE THIS PRODUCT LABEL

Norco

NORCO, INC.

898 W. Gowen Rd. • Boise, ID 83705

208-336-1643

USPUN1002

MEDICAL AIR

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:42602-004
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	23 L in 100 L

Inactive Ingredients

Ingredient Name	Strength
NITROGEN (UNII: N762921K75)	

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:42602-004-01	651.36 L in 1 CYLINDER		
2	NDC:42602-004-02	6513.6 L in 1 CYLINDER		
3	NDC:42602-004-03	8779.2 L in 1 CYLINDER		

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205820	09/01/2008	

Labeler - Norco, Inc. (043694645)

Registrant - Norco, Inc. (043694645)

Establishment

Name	Address	ID/FEI	Business Operations
Norco, Inc.		962460528	manufacture(42602-004)

Revised: 3/2014

Norco, Inc.