

**OXYGEN - oxygen gas**  
**Airtec Gases, LLC**

-----  
**Oxygen**

**OXYGEN COMPRESSED USP product label**

**OXYGEN, COMPRESSED USP UN 1072**

**OXYGEN 2**

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. **Produced by Air Liquefaction. DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 **DO NOT REMOVE THIS PRODUCT LABEL.**

DISTRIBUTED BY: **AIRTEC GASES**

LAS VEGAS, NV 89109

(702) 454-2400

LOT #:

NET CONTENTS:

ATG-01                    E15

**OXYGEN,  
COMPRESSED  
USP  
UN 1072**



**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen contents of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by **Air Liquefaction.**

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.

CAS:7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**

**DISTRIBUTED BY:**

***AIRTEC GASES***

LAS VEGAS, NV 89109

(702) 454-2400

**LOT #:**

**NET CONTENTS:**



ATG-01

E15

**OXYGEN COMPRESSED USP SL product label**

**OXYGEN, COMPRESSED USP UN 1072**

**AIRTEC GASES**

LAS VEGAS, NV 89109

(702) 454-2400

**OXYGEN 2 ATG03 LOT#**

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. **Produced by Air Liquefaction. DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 **DO NOT REMOVE THIS PRODUCT LABEL.**

NET CONTENTS:



**OXYGEN Refrigerated Liquid USP product label**

**Oxygen, Refrigerated Liquid, USP**

**UN1073 Rx ONLY**

**AIRTEC GASES**

LAS VEGAS, NV 89109

(702) 454-2400


**OXYGEN 2**

NET CONTENTS:

ATG04

**Rx ONLY. WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction of resuscitative equipment. **Produced by Air Liquefaction. DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDER, CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBELS IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only the equipment of compatible materials equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. **FIRST AID FIRST AID: IF ON SKIN:** Thaw affected parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL**



## OXYGEN

oxygen gas

### Product Information

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:24312-001
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
-----------------	-------------------	----------

<b>OXYGEN</b> (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L
-------------------------------------------------------------	--------	---------------

### Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:24312-001-01	113 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
2	NDC:24312-001-02	170 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
3	NDC:24312-001-03	248 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
4	NDC:24312-001-04	415 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
5	NDC:24312-001-05	682 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
6	NDC:24312-001-06	7132 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
7	NDC:24312-001-07	3552 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
8	NDC:24312-001-08	180 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/2004	
9	NDC:24312-001-09	647 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
10	NDC:24312-001-10	1724 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
11	NDC:24312-001-11	8510 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
12	NDC:24312-001-12	420 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
13	NDC:24312-001-13	690 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
14	NDC:24312-001-14	3160 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
15	NDC:24312-001-15	3470 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
16	NDC:24312-001-16	6270 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
17	NDC:24312-001-17	7060 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
18	NDC:24312-001-18	8510 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
19	NDC:24312-001-19	103.1 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
20	NDC:24312-001-20	149.7 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
21	NDC:24312-001-21	647.1 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
22	NDC:24312-001-22	1723.6 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
23	NDC:24312-001-23	248.4 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
24	NDC:24312-001-24	127100 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	
25	NDC:24312-001-25	141500 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/2004	

## Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205712	01/01/2004	

**Labeler** - Airtec Gases, LLC (167046148)

**Registrant** - Airtec Gases, LLC (167046148)

## Establishment

Name	Address	ID/FEI	Business Operations
Airtec Gases, LLC		167046148	manufacture(24312-001)

Revised: 10/2023

Airtec Gases, LLC