

**OXYGEN- oxygen gas**  
**A & B Welding Supply Co.**

**Oxygen Labels**

OXYGEN,  
COMPRESSED

USP

U.N. 1072

OXYGEN 2

17033 (R 04/05)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, RX ONLY. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Use in accordance with the Material Safety Data Sheet (MSDS).

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

DISTRIBUTED BY:

A and B WELDING SUPPLY CO.


RAPID CITY, S.D.

CONTENTS:                    LTRS:                    CU.FT.

**REFRIGERATED LIQUID**

**OXYGEN,  
REFRIGERATED  
LIQUID  
USP**

**UN1073**



**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑**  
**DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

**Produced by Air Liquefaction.**

**WARNING:** EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE.  
VIGOROUSLY ACCELERATES COMBUSTION.  
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.  
CAN CAUSE SEVERE FROSTBITE.  
Keep oil, grease, and combustibles away.  
Use only with equipment cleaned for oxygen service.  
Store and use with adequate ventilation.  
Do not get liquid in eyes, on skin, or clothing.  
For liquid withdrawal, wear face shield and gloves.  
Do not drop. Use suitable hand truck for container movement.  
Avoid spills. Do not walk on or roll equipment over spills.  
Cylinder temperature should not exceed 52°C (125°F).  
Close valve after each use and when empty.  
Use a back flow preventive device in the piping.  
Use in accordance with the **Material Safety Data Sheet (MSDS)**.

**FIRST AID:** IN CASE OF FROSTBITE, obtain medical treatment immediately.  
CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**

DISTRIBUTED BY:  
**A & B WELDING SUPPLY CO.**  
914 E CHICAGO ST. RAPID CITY, S.D. 57701  
605-343-5365

41523  
(R 10/04)

Oxygen,

Refrigerated

Liquid

USP

UN 1073

OXYGEN 2

LOT:

CONTENTS: LITERS

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE.

VIGOROUSLY ACCELERATES COMBUSTION.

COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use suitable hand truck for container movement.

Avoid spills. Do not walk on or roll equipment over spills.

Close valve after each use and when empty.

Use in accordance with Material Safety Data Sheet(MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx ONLY.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

DO NOT REMOVE THIS PRODUCT LABEL.


Filled and Distributed by:

A and B WELDING SUPPLY CO.

914 E. Chicago St.

RAPID CITY, S.D. 57701

605-343-5365



OXYGEN, COMPRESSED USP

UN1072

OXYGEN 2

Contents LTRS CU.FT.

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

**WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION.** Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Use in accordance with the Material Safety Data Sheet (MSDS). **DO NOT REMOVE THIS PRODUCT LABEL.**

FILLED AND DISTRIBUTED BY:

A and B WELDING SUPPLY CO., INC.

914 E CHICAGO ST. RAPID CITY, SD 57701

**OXYGEN,  
COMPRESSED  
USP**

**UN1072**



Contents \_\_\_\_\_

LTRS.

CU. FT.

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.  
Produced by Air Liquefaction.

**WARNING:** HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F). Use in accordance with the Material Safety Data Sheet (MSDS).  
CAS:7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

FILLED & DISTRIBUTED BY:

**A & B WELDING SUPPLY CO., INC.**

914 E. CHICAGO ST. RAPID CITY, SD 57701

605-343-5365

40033  
(R 09/05)

605-343-5365

## OXYGEN

oxygen gas

### Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:55728-001
Route of Administration	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

**Packaging**

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:55728-001-01	8070 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
2	NDC:55728-001-02	7050 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
3	NDC:55728-001-03	4360 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
4	NDC:55728-001-04	2350 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
5	NDC:55728-001-05	3284 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
6	NDC:55728-001-06	170 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
7	NDC:55728-001-07	124 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
8	NDC:55728-001-08	164 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
9	NDC:55728-001-09	425 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
10	NDC:55728-001-10	622 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
11	NDC:55728-001-11	160 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
12	NDC:55728-001-12	196 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	
13	NDC:55728-001-13	618893 L in 1 CYLINDER; Type 0: Not a Combination Product	01/02/1978	

**Marketing Information**

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205737	01/02/1978	

**Labeler** - A & B Welding Supply Co. (007499460)**Registrant** - A & B Welding Supply Co. (007499460)**Establishment**

Name	Address	ID/FEI	Business Operations
A & B Welding Supply Co.		007499460	manufacture(55728-001)