

**OXYGEN- oxygen gas**  
**Central Welding Supply Company**

-----  
**Oxygen**

OXYGEN, COMPRESSED USP

US1072

OXYGEN 2

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

**DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.** Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use.

**DO NOT REMOVE THIS PRODUCT LABEL.**

CAS: 7782-44-7

CONTENTS: LTRS: CU.FT.

CENTRAL WELDING SUPPLY

WWW.CENTRALWELDING.COM


1-800-697-0128

13305 38TH AVE NE

MARYSVILLE, WA 98271

IN CASE OF EMERGENCY CALL CHEMREC 800-424-9300

CONTENTS: LTRS: CU.FT.



REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP

UN1073

OXYGEN 2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS: LTRS. CU.FT

WARNING: USP For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

CENTRAL WELDING SUPPLY

WWW.CENTRALWELDING.COM

1-800-697-0182


13305 38TH AVE NE

MARYSVILLE, WA 98271

IN CASE OF EMERGENCY CALL CHEMREC 800-424-9300

**REFRIGERATED LIQUID**

**OXYGEN,  
REFRIGERATED  
LIQUID  
USP  
UN1073**



**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑  
DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

CONTENTS: \_\_\_\_\_

LTRS:   
CU.FT.

**WARNING:** **USP** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER.  
CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY.  
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

**FIRST AID:** **IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**



[www.centralwelding.com](http://www.centralwelding.com)

1-800-697-0128

13305 38th Ave NE  
MARYSVILLE, WA 98271



IN CASE OF EMERGENCY CALL CHEMTREC 800-424-9300

## OXYGEN

oxygen gas

### Product Information

Product Type	PRESCRIPTION ANIMAL DRUG	Item Code (Source)	NDC:70 151-002
Route of Administration	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

**Packaging**

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:70 151-002-01	420 L in 1 CYLINDER		
2	NDC:70 151-002-02	690 L in 1 CYLINDER		
3	NDC:70 151-002-03	2165 L in 1 CYLINDER		
4	NDC:70 151-002-04	3470 L in 1 CYLINDER		
5	NDC:70 151-002-05	4229 L in 1 CYLINDER		
6	NDC:70 151-002-06	6270 L in 1 CYLINDER		
7	NDC:70 151-002-07	7060 L in 1 CYLINDER		
8	NDC:70 151-002-08	8510 L in 1 CYLINDER		
9	NDC:70 151-002-09	2640 L in 1 CYLINDER		
10	NDC:70 151-002-10	38.6 L in 1 CYLINDER		
11	NDC:70 151-002-11	104.8 L in 1 CYLINDER		
12	NDC:70 151-002-12	150.1 L in 1 CYLINDER		
13	NDC:70 151-002-13	209.5 L in 1 CYLINDER		
14	NDC:70 151-002-14	589 L in 1 CYLINDER		
15	NDC:70 151-002-15	572 L in 1 CYLINDER		
16	NDC:70 151-002-16	1723.6 L in 1 CYLINDER		
17	NDC:70 151-002-17	590.6 L in 1 CYLINDER		
18	NDC:70 151-002-18	1252 L in 1 CYLINDER		
19	NDC:70 151-002-19	180 L in 1 CYLINDER		

**Marketing Information**

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141354	11/15/2015	

**Labeler** - Central Welding Supply Company (020232583)**Establishment**

Name	Address	ID/FEI	Business Operations
Central Welding Supply Company		020232583	manufacture

Revised: 11/2020

Central Welding Supply Company