

NITROGEN- nitrogen gas
Industrial Welding & Tool Supply, Ltd.

Nitrogen

NITROGEN, COMPRESSED NF UN1066. NON-FLAMMABLE GAS 2. Rx only. WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken. CAUTION: HIGH PRESSURE GAS. CAN CAUSE RAPID SUFFOCATION. Store and use with adequate ventilation. Use equipment rated for cylinder pressure. Use a back flow preventive device in the piping. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Close valve after each use and when empty. Use in accordance with the Material Safety Data Sheet (MSDS). FIRST AID: IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician. CAS: 7727-37-9. DO NOT REMOVE THIS PRODUCT LABEL. GAS AND SUPPLY 8595 W 81ST South. Tulsa, OK 74131 (918) 224-6455




REFRIGERATED LIQUID NITROGEN, FREFRIGERATED LIQUID NF. UN 1977. ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT CHANGE OR FORCE FIT CONNECTIONS. RX ONLY. WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications, and side effects and the precautions to be taken. WARNING: EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE. CAN CAUSE RAPID SUFFOCATION. CAN CAUSE SEVERE FROSTBITE. </content>
<content>Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS). FIRST AID: IF INHALED, remove to fresh air. If not breathing, give artificial

respiration. If breathing is difficult, give oxygen. Call a physician. IN CASE OF FROSTBITE, obtain medical treatment immediately. CAS: 7727-37-9. DO NOT REMOVE THIS PRODUCT LABEL. GAS AND SUPPLY 8595 W 81ST South. Tulsa, OK 74131 (918) 224-

REFRIGERATED LIQUID

**NITROGEN,
REFRIGERATED
LIQUID
NF**



UN1977

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

R_x only

WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken.

WARNING: EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE.
CAN CAUSE RAPID SUFFOCATION.
CAN CAUSE SEVERE FROSTBITE.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use suitable hand truck for container movement.

Cylinder temperature should not exceed 52°C (125°F).

Close valve after each use and when empty.

Use a back flow preventive device in the piping.

Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7727-37-9

DO NOT REMOVE THIS PRODUCT LABEL.



8595 W. 81ST South
Tulsa, OK 74131
(918)224-6455

43649
(05/06)

6455

NITROGEN

nitrogen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:58404-002
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
NITROGEN (UNII: N762921K75) (NITROGEN - UNII:N762921K75)	NITROGEN	995 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:58404-002-01	396 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
2	NDC:58404-002-02	651 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
3	NDC:58404-002-03	2973 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
4	NDC:58404-002-04	3256 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
5	NDC:58404-002-05	5946 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
6	NDC:58404-002-06	5412 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
7	NDC:58404-002-07	6626 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
8	NDC:58404-002-08	7220 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
9	NDC:58404-002-09	7900 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
10	NDC:58404-002-10	8608 L in 1 CYLINDER; Type 0: Not a Combination Product	05/01/2013	
11	NDC:58404-002-11	5097 L in 1 DEWAR; Type 0: Not a Combination Product	05/01/2013	
12	NDC:58404-002-12	5663 L in 1 DEWAR; Type 0: Not a Combination Product	05/01/2013	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205866	05/01/2013	

Labeler - Industrial Welding & Tool Supply, Ltd. (078785627)

Establishment

Name	Address	ID/FEI	Business Operations
Industrial Welding & Tool Supply, Ltd.		078785627	manufacture(58404-002)

Revised: 10/2022

Industrial Welding & Tool Supply, Ltd.