

OXYGEN- oxygen gas
Gallup Welders Supply, Inc.

Oxygen Labels

OXYGEN
REFRIGERATED LIQUID USP
UN1073

OXYGEN 2
ALWAYS KEEP CONTAINER IN UPRIGHT POSITION
DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING

For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE.

VIGOROUSLY ACCELERATES COMBUSTION.

COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin, or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use suitable hand truck for container movement.

Avoid spills. Do not walk on or roll equipment over spills.

Cylinder temperature should not exceed 52 degrees C (125 degrees F).

Close valve after each use and when empty.

Use a back flow preventive device in the piping.

Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

SECURE ALL CYLINDERS WHILE IN STORAGE AND IN USE.

DO NOT REMOVE THIS PRODUCT LABEL.

FOUR CORNERS

WELDING AND GAS SUPPLY

606 EAST HIGHWAY 66 GALLUP, NM 87301

505-722-3845

OXYGEN, REFRIGERATED LIQUID USP UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION!

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION.

COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease and combustibles away.

Use only with equipment cleaned for oxygen service.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin or clothing.

**SECURE ALL CYLINDERS WHILE IN STORAGE AND IN USE.
DO NOT REMOVE THIS PRODUCT LABEL.**



For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Container temperature should not exceed 52°C (125°F). Close valve after each use and when empty. Use a back flow preventive device in the piping.

Use in accordance with the Material Safety Data Sheet (MSDS).

• **IN CASE OF FROSTBITE,** obtain medical treatment immediately.

CAS: 7782-44-7

FOUR CORNERS

WELDING & GAS SUPPLY
606 EAST HIGHWAY 66 • GALLUP, NM 8731
505-722-3845

LABS-501205-04-1 1/81/2000 1001 0010

OXYGEN,
COMPRESSED
USP

UN1072

OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Use in accordance with the Material Safety Data Sheet (MSDS).

CAS NUMBER: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

FOUR CORNERS WELDING AND GAS SUPPLY


606 EAST HWY 66

GALLUP, NM 87301

CONTENTS:

LTRS:
CO.FT:

OXYGEN,
COMPRESSED
USP
UN1072



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, consult your physician. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquide. **WARNING:** HIGH PRESSURE. OILY GREASE GAS VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Close valve slowly. Store and use with adequate ventilation. Use only with equipment designed for Oxygen service and rated for cylinder pressure. Use a back flow prevention device in low piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F). Use in accordance with the Material Safety Data Sheet (MSDS). CAS: 7782-44-7

CONTENTS: LBS.
GAL.

4 CORNERS WELDING & GAS SUPPLY
606 EAST HWY 66
GALLUP, NM 87301

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:13826-001(NDC:10018-8999)
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:13826-001-01	9344 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1985	
2	NDC:13826-001-02	8495 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1985	
3	NDC:13826-001-03	6230 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1985	
4	NDC:13826-001-04	4247 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1985	
5	NDC:13826-001-05	3454 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1985	
6	NDC:13826-001-06	2265 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1985	
7	NDC:13826-001-07	1132 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1985	
8	NDC:13826-001-08	566 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1985	
9	NDC:13826-	639 L in 1 CYLINDER; Type 0: Not a Combination	01/01/1985	

9	001-09	Product	01/01/1985	
10	NDC:13826-001-10	424 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1985	
11	NDC:13826-001-11	254 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1985	
12	NDC:13826-001-12	169 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1985	
13	NDC:13826-001-13	113 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1985	
14	NDC:13826-001-14	127425 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1985	
15	NDC:13826-001-15	155742 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1985	
16	NDC:13826-001-16	325926 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1985	
17	NDC:13826-001-17	387855 L in 1 DEWAR; Type 0: Not a Combination Product	01/01/1985	
18	NDC:13826-001-18	410 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1985	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205865	01/01/1985	

Labeler - Gallup Welders Supply, Inc. (097968531)

Establishment

Name	Address	ID/FEI	Business Operations
Gallup Welders Supply, Inc.		097968531	manufacture(13826-001)

Establishment

Name	Address	ID/FEI	Business Operations
Gallup Welders Supply, Inc.		619216591	manufacture(13826-001)

Establishment

Name	Address	ID/FEI	Business Operations
Gallup Welders Supply, Inc.		807672449	repack(13826-001)

Revised: 10/2023

Gallup Welders Supply, Inc.