

NITROGEN- nitrogen gas
A & B Welding Supply Co.

Nitrogen

NITROGEN, Refrigerated Liquid
UN1977
CAS 7727-37-9
NON-FLAMMABLE GAS 2

Nitrogen, NF

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION
DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING: EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE.
CAN CAUSE RAPID SUFFOCATION.

CAN CAUSE SEVERE FROSTBITE.

Store and use with adequate ventilation.

Do not get liquid in eyes, on skin or clothing.

For liquid withdrawal, wear face shield and gloves.

Do not drop. Use hand truck for container movement.

Container temperature should not exceed 52oC(125oF).

Close valve after each use and when empty.

Use a back flow preventive device in the piping.

Use in accordance with Material Safety Data Sheet.

FIRST AID: IF INHALED, remove to fresh air. If not breathing, give artificial respiration.
If breathing is difficult, give oxygen. Call a physician.

IN CASE OF FROSTBITE, obtain medical treatment immediately.

Rx Only

WARNING: Administration of nitrogen may be hazardous or contraindicated. For use by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

DO NOT REMOVE THIS LABEL.

A and B Welding Supply Co. Inc.
605-343-5365
914 East Chicago Street
PO Box 2053

NITROGEN, Refrigerated Liquid

UN1977

CAS 7727-37-9



Nitrogen, NF

**ALWAYS KEEP CONTAINER IN UPRIGHT POSITION
DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

WARNING: EXTREMELY COLD LIQUID AND GASES UNDER PRESSURE.
~~CAN CAUSE RAPID SUFFOCATION.~~
~~CAN CAUSE SEVERE FROSTBITE.~~
Store and use with adequate ventilation.
Do not get liquid in eyes, on skin or clothing.
For liquid withdrawal, wear face shield and gloves.
Do not drop. Use hand truck for container movement.
Container temperature should not exceed 52°C (125°F).
Close valve after each use and when empty.
Use a back flow preventive device in the piping.
Use in accordance with Material Safety Data Sheet.

FIRST AID: IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

IN CASE OF FROSTBITE, obtain medical treatment immediately.

Rx Only

WARNING: Administration of nitrogen may be hazardous or contraindicated. For use by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

DO NOT REMOVE THIS LABEL.

A & B Welding Supply Co. Inc.

605-343-5365

914 East Chicago Street

PO Box 2053

Rapid City, SD 57709

(Rev.1 Dec 11)

Contents: _____

Rapid City, SD 57709 Contents:

NITROGEN, COMPRESSED NF

UN 1066

NON-FLAMMABLE GAS 2


Rx only. **WARNING:** Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and precautions to be taken. **WARNING:** CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Use a back flow preventive device in the piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceed 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use. **FIRST AID:** IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention. CAS: 7727-37-9

DO NOT REMOVE THIS PRODUCT LABEL.

A&B Welding Supply Co., Inc.

914 W Chicago Street

Rapid City, SD 57701
605-343-5365
CONTENTS: LTRS CU FT



FILLED AND DISTRIBUTED BY:
A AND B WELDING SUPPLY CO., INC
914 E CHICAGO ST
RAPID CITY, SD 57701
605-343-5365
NITROGEN, REFRIGERATED LIQUID NF
UN 1977

NON-FLAMMABLE GAS 2
ALWAYS KEEP CONTAINER IN UPRIGHT POSITION
DO NOT CHANGE OR FORCE FIT CONNECTIONS

Rx only. **WARNING:** Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects and the precautions to be taken.

WARNING: EXTREMELY COLD LIQUID AND GAS UNDER PRESSURE. CAN CAUSE RAPID SUFFOCATION. CAN CAUSE SEVERE FROSTBITE. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. cylinder temperature should not exceed 52 degrees C (125 degrees F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give Oxygen. Call a physician. IN CASE OF FROSTBITE, obtain medical treatment immediately. CAS 7727-37-9

12	NDC:55728-200-12	7787 L in 1 CYLINDER; Type 0: Not a Combination Product	01/09/2012	
Marketing Information				
Marketing Category	Application Number or Monograph Citation		Marketing Start Date	Marketing End Date
NDA	NDA205766		01/09/2012	

Labeler - A & B Welding Supply Co. (007499460)

Establishment			
Name	Address	ID/FEI	Business Operations
A & B Welding Supply Co.		007499460	manufacture(55728-200)

Revised: 10/2023

A & B Welding Supply Co.