

OXYGEN- oxygen gas
Mitchell Home Medical, Inc.

Oxygen Label

OXYGEN, COMPRESSED USP
UN 1072
OXYGEN2

WARNING: For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. **WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION.** Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Close valve after each use and when empty. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Use in accordance with the Material Safety Data Sheet (MSDS). CAS: 7782-44-7. RETURN WITH 25 PSIG. DO NOT REMOVE THIS PRODUCT LABEL.

ANN ARBOR WELDING SUPPLY
4811 CARPENTER ROAD. YPSILANTI, MI 48197
734-572-0444

SIZE: H

Property of: Ann Arbor Welding Supply/Mitchell Home Medical (800) 420-0202



OXYGEN, COMPRESSED USP

UN 1072

OXYGEN2

Contents LTRS CU.FT.

WARNING: For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Close valve after each use and when empty. Cylinder temperature should not exceed 52 degrees C (125 degrees F). Use in accordance with the Material Safety Data Sheet (MSDS). CAS: 7782-44-7. DO NOT REMOVE THIS PRODUCT LABEL.

ANN ARBOR WELDING SUPPLY

4811 CARPENTER ROAD. YPSILANIT, MI 48197

734-572-0444

SIZE: AA

Property of: Ann Arbor Welding Supply/Mitchell Home Medical (800) 420-0202

**OXYGEN,
COMPRESSED
USP**

UN1072

Contents _____

LTRS.
CU.FT.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52°C (125°F). Use in accordance with the **Material Safety Data Sheet (MSDS)**. CAS:7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

ANN ARBOR WELDING SUPPLY
4811 CARPENTER ROAD · YPSILANTI, MI 48197
734-572-0444

40033
(R 09/05)

81202

Property Of:
Ann Arbor
Welding Supply/
Mitchell Home
Medical
(800) 420-0202

Size:
AA

Produced by air liquefaction

OXYGEN, COMPRESSED USP

UN 1072

OXYGEN2

WARNING: For emergency use only when administered by properly trained personnel for Oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of Oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. WARNING: HIGH

PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Use only with pressure reducing equipment and apparatus designed for Oxygen. Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects, free of oil and grease to avoid violent ignition. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act. Pursuant to recommendations by Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 125 degrees F. DO NOT REMOVE THIS PRODUCT LABEL. Use a back flow preventive device in the piping. Use only in accordance with product instructions and Material Safety Data Sheet

SIZE: AA

Contents at 70 degrees F. 9 cu.ft. at 2015 PSI. 248 Liters at 2015 PSI.

Manufactured By:

ARBOR SPECIALTY GASES

A DIVISION OF Ann Arbor Welding Supply

4811 CARPENTER ROAD. YPSILANIT, MI 48197

866-528-9960

Produced by air liquefaction

**OXYGEN
COMPRESSED
U.S.P. UN 1072**

OXYGEN
2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications: **Rx ONLY.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

**WARNING: HIGH PRESSURE OXIDIZING GAS
VIGOROUSLY ACCELERATES COMBUSTION**

- Use only with pressure reducing equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure.
- Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects, free of oil and grease to avoid violent ignition.
- Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.
- Pursuant to recommendations by Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 125°F.
- **DO NOT REMOVE THIS PRODUCT LABEL.**
Use a back flow preventive device in the piping.
Use only in accordance with product instructions and material safety data sheet.

Date code: 0406 Label: 0035-429

Size
AA

Contents at 70°F:
9 Cu.Ft. at 2015 PSI
248 Liters at 2015 PSI

Manufactured By:

Arbor Specialty Gases
A Division of: **Ann Arbor Welding Supply**

4811 Carpenter Road • Ypsilanti, MI 48197 • (866) 528-9960

REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx Only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE.

VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE. Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin, or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52C (125F). Close

valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS). FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately. CAS: 7782-44-7
DO NOT REMOVE THIS PRODUCT LABEL.

Arbor Specialty Gases

4811 CARPENTER ROAD, YPSILANTI, MI 48197

REFRIGERATED LIQUID

**OXYGEN,
REFRIGERATED
LIQUID
USP**



UN1073

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑

DO NOT CHANGE OR FORCE FIT CONNECTIONS.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE.
VIGOROUSLY ACCELERATES COMBUSTION.
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.
CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.
Use only with equipment cleaned for oxygen service.
Store and use with adequate ventilation.
Do not get liquid in eyes, on skin, or clothing.
For liquid withdrawal, wear face shield and gloves.
Do not drop. Use suitable hand truck for container movement.
Avoid spills. Do not walk on or roll equipment over spills.
Cylinder temperature should not exceed 52°C (125°F).
Close valve after each use and when empty.
Use a back flow preventive device in the piping.
Use in accordance with the **Material Safety Data Sheet (MSDS)**.

FIRST AID: **IN CASE OF FROSTBITE,** obtain medical treatment immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.



Arbor Specialty Gases

4811 CARPENTER ROAD • YPSILANTI, MI 48197

 (866) 528-9960

41533
(R 10/04)

OXYGEN, REFRIGERATED LIQUID USP UN1073 (CRYOGENIC LIQUID) OXYGEN 2

Produced by Air Liquefaction

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

WARNING: WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE. For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx Only. WARNING! Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin, or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the Material Safety Data Sheet (MSDS). WARNING: Caution Federal Law Prohibits Dispensing without Prescription.

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately. PLEASE REFER TO THE MATERIAL SAFETY DATA SHEET FOR SAFETY AND PRODUCT INFORMATION.

Company Name:

Lot Number:

Contents:

Expiration Date:

DO NOT REMOVE THIS PRODUCT LABEL.

OXYGEN

REFRIGERATED LIQUID, U.S.P.
UN 1073
(CRYOGENIC LIQUID)

Produced by Air Liquefaction



ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING

WARNING!
EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, RX only.

WARNING: Caution Federal Law Prohibits Dispensing without Prescription.

WARNING!
Uninterrupted use of high concentrations of oxygen over long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment. Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Use in accordance with Material Safety Data Sheet.

FIRST AID

IN CASE OF FROSTBITE, obtain medical treatment immediately.

PLEASE REFER TO THE MATERIAL SAFETY DATA SHEET FOR SAFETY AND PRODUCT INFORMATION.

Company Name:

Lot Number:

Contents:

Expiration Date:

FIRST AID

DO NOT REMOVE THIS PRODUCT LABEL

PART 408 48P
PRINTED BY WATERMANN MFG INC. 325-440-1248

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:10867-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date

1	NDC:10867-001-01	255 L in 1 CYLINDER; Type 0: Not a Combination Product	10/01/2004	
2	NDC:10867-001-02	368 L in 1 CYLINDER; Type 0: Not a Combination Product	10/01/2004	
3	NDC:10867-001-03	680 L in 1 CYLINDER; Type 0: Not a Combination Product	10/01/2004	
4	NDC:10867-001-04	7108 L in 1 CYLINDER; Type 0: Not a Combination Product	10/01/2004	
5	NDC:10867-001-05	3540 L in 1 CYLINDER; Type 0: Not a Combination Product	10/01/2004	
6	NDC:10867-001-06	170 L in 1 CYLINDER; Type 0: Not a Combination Product	10/01/2004	
7	NDC:10867-001-07	387853 L in 1 CYLINDER; Type 0: Not a Combination Product	10/01/2004	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205889	10/01/2004	

Labeler - Mitchell Home Medical, Inc. (001025878)

Establishment

Name	Address	ID/FEI	Business Operations
Mitchell Home Medical, Inc.		001025878	manufacture(10867-001)

Revised: 11/2019

Mitchell Home Medical, Inc.