NITROGEN- nitrogen gas American Welding & Gas

Nitrogen

NITROGEN, REGRIGERATED LIQUID UN 1977 MEDICAL NITROGEN, NF RX only.

WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTRAINS REGRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.

Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. Use a back flow preventive device in the piping. DO NOT change or force fit connections. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN: That frosted parts with lukewarm water. Do not rub affected area. Get immediate medical administration.

AMERICAN WELDING & GAS, INC.
113 N. SHORECREST ROAD
COLUMBIA, SC 29209
803-567-2772
WWW.AMWELDING.COM
DO NOT REMOVE THIS PRODUCT LABEL.




NITROGEN, COMPRESSED NF UN 1066 MEDICAL NITROGEN. N.F.

RX only. WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use. FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

CAS: 7727-37-9
DO NOT REMOVE THIS PRODUCT LABEL.
SG-267 V001 (02/17)
AMERICAN WELDING & GAS, INC.
113 N. SHORECREST ROAD
COLUMBIA, SC 29209
803-567-2772
WWW.AMWELDING.COM
PRINTED IN THE U.S.A



NITROGEN, COMPRESSED NF

UN1066

CONTENTS

CYLINDER TYPE CU. FT. LITERS CYLINDER TYPE CU. FT. LITERS

T 275 7801 G 34 957

K 207 5863 E 23 643

M 107 303

MEDICAL NITROGEN, NF

WARNING: Rx only. Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Use a back flow preventive device in the piping. Close after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

CAS: 7727-37-9

DO NOT REMOVE THIS PRODUCT LABEL.


AWG

American Welding & Gas, Inc.

4900 Falls of Neuse Road, Suite 150

Raleigh, NC 27609

800-967-6874



NITROGEN, COMPRESSED NF

UN1066

CONTENTS

CYLINDER TYPE CU. FT. LITERS CYLINDER TYPE CU. FT. LITERS

T 275 7801 G 34 957

K 207 5863 E 23 643

M 107 303

MEDICAL NITROGEN, NF

WARNING: Rx only. Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in

the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Use a back flow preventive device in the piping. Close after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

CAS: 7727-37-9

DO NOT REMOVE THIS PRODUCT LABEL.

AWG

American Welding & Gas, Inc. 4900 Falls of Neuse Road, Suite 150 Raleigh, NC 27609 800-967-6874

NITROGEN, COMPRESSED





CONTENTS

CYLINDER Type	CU. FT.	LITERS
	275	7801
□ K	207	5863
□ M	107	3030

CYLINDER Type	CU. FT.	LITERS
□ G	34	957
□E	23	643

MEDICAL NITROGEN, NF

WARNING: Rx Only. Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical

advice/attention.

CAS: 7727-37-9 DO NOT REMOVE THIS PRODUCT LABEL.



American Welding & Gas, Inc.

4900 Falls of Neuse Road, Suite 150 Raleigh, NC 27609

800-967-6874

NITROGEN

nitrogen gas

Product Information

HUMAN PRESCRIPTION DRUG NDC:44076-006 **Product Type** Item Code (Source) RESPIRATORY (INHALATION) **Route of Administration**

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
NITROGEN (UNII: N762921K75) (NITROGEN - UNII:N762921K75)	NITROGEN	990 mL in 1 L

P	ackaging			
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:44076-006- 15	255 L in 1 CYLINDER; Type 0: Not a Combination Product	04/01/2007	
	NDC:44076-006- 16	3640 L in 1 DEWAR; Type 0: Not a Combination Product	04/01/2007	

3	NDC:44076-006- 17	4551 L in 1 DEWAR; Type 0: Not a Combination Product	04/01/2007	
4	NDC:44076-006- 18	3588 L in 1 DEWAR; Type 0: Not a Combination Product	04/01/2007	
5	NDC:44076-006- 19	5658 L in 1 DEWAR; Type 0: Not a Combination Product	04/01/2007	
	NDC:44076-006- 20	3685 L in 1 DEWAR; Type 0: Not a Combination Product	04/01/2007	
7	NDC:44076-006- 21	4099 L in 1 DEWAR; Type 0: Not a Combination Product	04/01/2007	

Marketing Information					
MarketingApplication Number or MonographMarketing StartMarketing EndCategoryCitationDateDate					
NDA	NDA205839	04/01/2007			

Labeler - American Welding & Gas (068181965)

Establishment				
Name	Address	ID/FEI	Business Operations	
AMERICAN WELDING AND GAS INC.		037335791	transfill(44076-006)	

Establishment				
Name	Address	ID/FEI	Business Operations	
AMERICAN WELDING & GAS, INC.		042196668	transfill(44076-006)	

Establishment			
Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		080591151	manufacture(44076-006)

Establishment				
Name	Address	ID/FEI	Business Operations	
AMERICAN WELDING & GAS, INC.		086189198	manufacture(44076-006)	

Establishment			
Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		096401170	manufacture(44076-006)

Establishment				
Name	Address	ID/FEI	Business Operations	
AMERICAN WELDING & GAS. INC.		116724243	manufacture(44076-006)	

Establishment			
Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		116933887	manufacture(44076-006)

Establishment			
Name	Address	ID/FEI	Business Operations
American Welding and Gas Inc.		118027602	transfill(44076-006)

Establishment			
Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		118697324	manufacture(44076-006)

Establishment			
Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		806534954	manufacture(44076-006)

Establishment				
Name	Address	ID/FEI	Business Operations	
AMERICAN WELDING & GAS, INC.		828380738	manufacture(44076-006)	

Establishment			
Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		829720098	manufacture(44076-006)

Establishment			
Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		869461520	transfill(44076-006)

Establishment				
Name	Address	ID/FEI	Business Operations	
American Welding & Gas, Inc.		119199574	manufacture(44076-006)	

Revised: 4/2024 American Welding & Gas