

NITROGEN- nitrogen gas
American Welding & Gas

Nitrogen

NITROGEN, REGRIGERATED LIQUID UN 1977

MEDICAL NITROGEN, NF

RX only.

WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTRAINS REGRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.

Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. Use a back flow preventive device in the piping. DO NOT change or force fit connections. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN: That frosted parts with lukewarm water. Do not rub affected area. Get immediate medical administration.

AMERICAN WELDING & GAS, INC.


113 N. SHORECREST ROAD

COLUMBIA, SC 29209

803-567-2772

WWW.AMWELDING.COM

DO NOT REMOVE THIS PRODUCT LABEL.



NITROGEN, COMPRESSED NF UN 1066 MEDICAL NITROGEN, N.F.

RX only. WARNING: Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 degrees C (125 degrees F). Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

CAS: 7727-37-9

DO NOT REMOVE THIS PRODUCT LABEL.

SG-267 V001 (02/17)

AMERICAN WELDING & GAS, INC.


113 N. SHORECREST ROAD

COLUMBIA, SC 29209

803-567-2772

WWW.AMWELDING.COM

PRINTED IN THE U.S.A



NITROGEN, COMPRESSED NF

UN1066

CONTENTS

CYLINDER TYPE CU. FT. LITERS CYLINDER TYPE CU. FT. LITERS

T 275 7801 G 34 957

K 207 5863 E 23 643

M 107 303

MEDICAL NITROGEN, NF

WARNING: Rx only. Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Use a back flow preventive device in the piping. Close after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

CAS: 7727-37-9

DO NOT REMOVE THIS PRODUCT LABEL.

AWG

American Welding & Gas, Inc.

4900 Falls of Neuse Road, Suite 150

Raleigh, NC 27609

800-967-6874

**NITROGEN,
COMPRESSED
NF**



UN1066

CONTENTS

CYLINDER TYPE	CU. FT.	LITERS
<input type="checkbox"/> T	275	7801
<input type="checkbox"/> K	207	5863
<input type="checkbox"/> M	107	3030

CYLINDER TYPE	CU. FT.	LITERS
<input type="checkbox"/> G	34	957
<input type="checkbox"/> E	23	643
<input type="checkbox"/> _____	_____	_____

MEDICAL NITROGEN, NF

WARNING: **Rx Only.** Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

CAS: 7727-37-9

DO NOT REMOVE THIS PRODUCT LABEL.



American Welding & Gas, Inc.


4900 Falls of Neuse Road, Suite 150

Raleigh, NC 27609

800-967-6874

AWG-203
V002

NITROGEN,
COMPRESSED
NF



UN1066

CONTENTS

CYLINDER TYPE	CU. FT.	LITERS
<input type="checkbox"/> T	275	7801
<input type="checkbox"/> K	207	5863
<input type="checkbox"/> M	107	3030

CONTENTS

CYLINDER TYPE	CU. FT.	LITERS
<input type="checkbox"/> G	34	957
<input type="checkbox"/> E	23	643
<input type="checkbox"/> _____	_____	_____

MEDICAL NITROGEN, NF


WARNING: Rx Only. Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

CAS: 7727-37-9

DO NOT REMOVE THIS PRODUCT LABEL.



American Welding & Gas, Inc.

4900 Falls of Neuse Road, Suite 150
Raleigh, NC 27609
800-967-6874

AWG-203
V002

NITROGEN, COMPRESSED NF

UN1066

CONTENTS

CYLINDER TYPE CU. FT. LITERS CYLINDER TYPE CU. FT. LITERS

T 275 7801 G 34 957

K 207 5863 E 23 643

M 107 303

MEDICAL NITROGEN, NF

WARNING: Rx only. Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Use a back flow preventive device in the piping. Close after each use and when empty.

Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

CAS: 7727-37-9

DO NOT REMOVE THIS PRODUCT LABEL.



AWG

American Welding & Gas, Inc.

4900 Falls of Neuse Road, Suite 150

Raleigh, NC 27609

800-967-6874

NITROGEN, COMPRESSED NF																									
UN1066																									
CONTENTS																									
<table><tr><th>CYLINDER TYPE</th><th>CU. FT.</th><th>LITERS</th></tr><tr><td><input type="checkbox"/> T</td><td>275</td><td>7801</td></tr><tr><td><input type="checkbox"/> K</td><td>207</td><td>5863</td></tr><tr><td><input type="checkbox"/> M</td><td>107</td><td>3030</td></tr></table>	CYLINDER TYPE	CU. FT.	LITERS	<input type="checkbox"/> T	275	7801	<input type="checkbox"/> K	207	5863	<input type="checkbox"/> M	107	3030	<table><tr><th>CYLINDER TYPE</th><th>CU. FT.</th><th>LITERS</th></tr><tr><td><input type="checkbox"/> G</td><td>34</td><td>957</td></tr><tr><td><input type="checkbox"/> E</td><td>23</td><td>643</td></tr><tr><td><input type="checkbox"/> _____</td><td>_____</td><td>_____</td></tr></table>	CYLINDER TYPE	CU. FT.	LITERS	<input type="checkbox"/> G	34	957	<input type="checkbox"/> E	23	643	<input type="checkbox"/> _____	_____	_____
CYLINDER TYPE	CU. FT.	LITERS																							
<input type="checkbox"/> T	275	7801																							
<input type="checkbox"/> K	207	5863																							
<input type="checkbox"/> M	107	3030																							
CYLINDER TYPE	CU. FT.	LITERS																							
<input type="checkbox"/> G	34	957																							
<input type="checkbox"/> E	23	643																							
<input type="checkbox"/> _____	_____	_____																							
MEDICAL NITROGEN, NF																									
WARNING: Rx Only. Administration of Nitrogen may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Nitrogen and is familiar with the indications, effects, dosages, methods, and frequency, and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.																									
WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. Do not handle until all safety precautions have been read and understood. Use and store only outdoors or in a well-ventilated place. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Use a back flow preventive device in the piping. Close valve after each use and when empty. Use only with equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Read and follow the Safety Data Sheet (SDS) before use.																									
FIRST AID: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.																									
CAS: 7727-37-9																									
DO NOT REMOVE THIS PRODUCT LABEL.																									
	American Welding & Gas, Inc. 4900 Falls of Neuse Road, Suite 150 Raleigh, NC 27609 800-967-6874																								
AWG-203 V002																									

NITROGEN

nitrogen gas

Product Information

Product Type

PRESCRIPTION ANIMAL DRUG

Item Code (Source)

NDC:44076-016

Route of Administration		RESPIRATORY (INHALATION)		
Active Ingredient/Active Moiety				
Ingredient Name		Basis of Strength	Strength	
Nitrogen (UNII: N762921K75) (Nitrogen - UNII:N762921K75)		Nitrogen	990 mL in 1 L	
Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:44076-016-15	255 L in 1 CYLINDER		
2	NDC:44076-016-16	3640 L in 1 DEWAR		
3	NDC:44076-016-17	4551 L in 1 DEWAR		
4	NDC:44076-016-18	3588 L in 1 DEWAR		
5	NDC:44076-016-19	5658 L in 1 DEWAR		
6	NDC:44076-016-20	3685 L in 1 DEWAR		
7	NDC:44076-016-21	4099 L in 1 DEWAR		
Marketing Information				
Marketing Category	Application Number or Monograph Citation		Marketing Start Date	Marketing End Date
NADA	NADA141381		04/01/2007	

Labeler - American Welding & Gas (068181965)

Establishment

Name	Address	ID/FEI	Business Operations
AMERICAN WELDING AND GAS INC.		037335791	transfill

Establishment

Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		042196668	transfill

Establishment

Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		080591151	manufacture

Establishment

Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		086189198	manufacture

Establishment

Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		096401170	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		116724243	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		116933887	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
American Welding and Gas Inc.		118027602	transfill

Establishment			
Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		118697324	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		806534954	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		828380738	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		829720098	manufacture

Establishment			
Name	Address	ID/FEI	Business Operations
AMERICAN WELDING & GAS, INC.		869461520	transfill

Establishment			
Name	Address	ID/FEI	Business Operations
American Welding & Gas, Inc.		119199574	manufacture