

OXYGEN- oxygen gas
BUCKEYE WELDING SUPPLY COMPANY, INC.

Oxygen

OXYGEN, COMPRESSED USP

UN1072


WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

Buckeye Welding Supply

360 East 8th Street. Greeley, CO 80631

In case of Emergency Call

800-255-3924



OXYGEN REFRIGERATED LIQUID, USP

UN1073

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING

USP

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

Keep out of reach of children; and Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

DANGER

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do

so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position.

READ AND FOLLOW THE SAFETY DATA SHEET (SDS) BEFORE USE.

CAS: 7782-44-7

IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

Lot Number:

Contents:

Expiration Date:

BUCKEYE WELDING SUPPLY


GREELY, CO

970-356-7546

DO NOT REMOVE THIS PRODUCT LABEL.

OXYGEN

REFRIGERATED LIQUID, USP
UN 1073



ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING

USP

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.


Produced by Air Liquefaction. Keep out of reach of children; and Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

READ AND FOLLOW THE SAFETY DATA SHEET (SDS) BEFORE USE.
CAS: 7782-44-7

DANGER

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.


Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position.



IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

Lot Number:
Contents:
Expiration Date:

BUCKEYE WELDING SUPPLY
GREELY, CO
(970) 356 - 7546



FIRST AID

DO NOT REMOVE THIS PRODUCT LABEL

PRINTED BY HATENBACH MFG., INC.
www.hatenbach.com

OXYGEN

oxygen gas

Product Information

Product Type

HUMAN PRESCRIPTION
DRUG

Item Code (Source)

NDC:53729-0002(NDC:11054-
009)

Route of Administration

RESPIRATORY

Route of Administration		(INHALATION)	
Active Ingredient/Active Moiety			
Ingredient Name		Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)		OXYGEN	992 mL in 1 L
Packaging			
#	Item Code	Package Description	Marketing Start Date
1	NDC:53729-0002-1	170 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987
2	NDC:53729-0002-2	248 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987
3	NDC:53729-0002-4	670 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987
4	NDC:53729-0002-3	410 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987
5	NDC:53729-0002-5	3894 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987
6	NDC:53729-0002-6	7107 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987
7	NDC:53729-0002-7	9514 L in 1 CYLINDER; Type 0: Not a Combination Product	09/01/1987
8	NDC:53729-0002-8	180 L in 1 DEWAR; Type 0: Not a Combination Product	09/01/1987
Marketing Information			
Marketing Category	Application Number or Monograph Citation		Marketing Start Date
NDA	NDA205827		09/01/1987

Labeler - BUCKEYE WELDING SUPPLY COMPANY, INC. (095156451)

Establishment			
Name	Address	ID/FEI	Business Operations
BUCKEYE WELDING SUPPLY COMPANY, INC.		095156451	manufacture(53729-0002) , transfill(53729-0002)

Establishment			
Name	Address	ID/FEI	Business Operations
BUCKEYE WELDING SUPPLY COMPANY, INC.		825593908	repack(53729-0002)