

**OXYGEN- oxygen gas**  
**Precision Oxygen & Supply**

**Oxygen**

Precision Oxygen & Supply Co., Inc. 4927 East 5th Street Austin, TX 78702 512-385-2247

OXYGEN, COMPRESSED UN1072

DO NOT REMOVE THIS PRODUCT LABEL OXYGEN 2 OXYGEN\* USP

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with Pressure reducing equipment and apparatus designed for Oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52° C (125°F). Use in accordance with the Material Safety Data Sheet (MSDS).

CAS: 7782-44-7 \* PRODUCED BY AIR LIQUEFACTION RETURN WITH 25 PSIG

OX MH 6400 LITERS OX E 705 LITER OX D 425 LITERS OX M6 141 LITERS OX \_\_\_\_ CF



REFRIGERATED LIQUID OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2  
ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT CHANGE OR FORCE FIT CONNECTION.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patents who have stopped breathing, unless use in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE. Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid

spills. Cylinder temperature should not exceed 52°C (125°F). Close valve after each use and when empty. Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

Precision Oxygen & Supply Co., Inc. 4927 East 5th Street Austin, TX 78702 512-385-2247

## REFRIGERATED LIQUID

**OXYGEN,  
REFRIGERATED  
LIQUID  
USP**



**UN1073**

**↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑  
DO NOT CHANGE OR FORCE FIT CONNECTIONS.**

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

**Produced by Air Liquefaction.**

**WARNING:** EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE.  
VIGOROUSLY ACCELERATES COMBUSTION.  
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.  
CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.  
Use only with equipment cleaned for oxygen service.  
Store and use with adequate ventilation.  
Do not get liquid in eyes, on skin, or clothing.  
For liquid withdrawal, wear face shield and gloves.  
Do not drop. Use suitable hand truck for container movement.  
Avoid spills. Do not walk on or roll equipment over spills.  
Cylinder temperature should not exceed 52°C (125°F).  
Close valve after each use and when empty.  
Use a back flow preventive device in the piping.  
Use in accordance with the **Material Safety Data Sheet (MSDS)**.

**FIRST AID:** IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

**DO NOT REMOVE THIS PRODUCT LABEL.**

**PO<sub>2</sub> Precision Oxygen  
& Supply Co., Inc.**  
4927 East 5th Street • Austin, TX 78702  
512-385-2247

41533  
(R 10/04)

**OXYGEN**

oxygen gas

**Product Information**

|                                |                          |                           |               |
|--------------------------------|--------------------------|---------------------------|---------------|
| <b>Product Type</b>            | PRESCRIPTION ANIMAL DRUG | <b>Item Code (Source)</b> | NDC:70097-011 |
| <b>Route of Administration</b> | RESPIRATORY (INHALATION) |                           |               |

**Active Ingredient/Active Moiety**

| <b>Ingredient Name</b>                               | <b>Basis of Strength</b> | <b>Strength</b> |
|--|--------------------------|-----------------|
| OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065) | OXYGEN                   | 990 mL in 1 L   |

**Packaging**

| <b>#</b> | <b>Item Code</b> | <b>Package Description</b> | <b>Marketing Start Date</b> | <b>Marketing End Date</b> |
|----------|------------------|----------------------------|-----------------------------|---------------------------|
| 1        | NDC:70097-011-01 | 6400 L in 1 CYLINDER       |                             |                           |
| 2        | NDC:70097-011-02 | 705 L in 1 CYLINDER        |                             |                           |
| 3        | NDC:70097-011-03 | 425 L in 1 CYLINDER        |                             |                           |
| 4        | NDC:70097-011-04 | 141 L in 1 CYLINDER        |                             |                           |
| 5        | NDC:70097-011-05 | 180 L in 1 DEWAR           |                             |                           |
| 6        | NDC:70097-011-06 | 240 L in 1 DEWAR           |                             |                           |

**Marketing Information**

| <b>Marketing Category</b> | <b>Application Number or Monograph Citation</b> | <b>Marketing Start Date</b> | <b>Marketing End Date</b> |
|---------------------------|---|-----------------------------|---------------------------|
| NADA                      | NADA141354                                      | 01/01/2004                  |                           |

**Labeler** - Precision Oxygen & Supply (078505617)**Establishment**

| <b>Name</b>               | <b>Address</b> | <b>ID/FEI</b> | <b>Business Operations</b> |
|---------------------------|----------------|---------------|----------------------------|
| Precision Oxygen & Supply |                | 078505617     | manufacture                |

Revised: 9/2016

Precision Oxygen &amp; Supply