

OXYGEN- oxygen gas
GIBBS WELDING SUPPLY, INC.

oxygen

OXYGEN, COMPRESSED USP UN1072 OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. PRODUCED BY AIR LIQUIFACTION

DANGER: MAY CAUSE OR INTENCIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL CONTENTS: LTRS: CU. FT.
GIBBS WELDING SUPPLY, INC. 875 VISCO DRIVE, NASHVILLE, TN 37210 (615) 254-1457 GW-1



OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2

GIBBS WELDING SUPPLY, INC. 875 VISCO DRIVE, NASHVILLE, TN 37210 (615) 254-1457

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this

container be filled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction.

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills, Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. **DO NOT REMOVE THIS PRODUCT LABEL.**

CAS: 7782-44-7



OXYGEN, COMPRESSED USP UN1072 OXYGEN 2 CAS: 7782-44-7

GIBBS WELDING SUPPLY, INC. 875 VISCO DRIVE, NASHVILLE, TN 37210 (615) 254-1457

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

DO NOT REMOVE THIS PRODUCT LABEL

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

Size Contents Size Contents M6 170 Liters E 682 Liters C 248 Liters H 6910 Liters D 415

**OXYGEN,
COMPRESSED
USP
UN 1072**

**OXYGEN
2**

C.A.S. NO. 7782-44-7

GIBBS WELDING SUPPLY, INC.
875 VISCO DRIVE, NASHVILLE, TN 37210
(615) 254-1457 GW-3

⚠ DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use. **DO NOT REMOVE THIS PRODUCT LABEL.**

⚠ WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only.** Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

Size	Contents	Size	Contents
<input type="checkbox"/> M6	170 Liters	<input type="checkbox"/> E	682 Liters
<input type="checkbox"/> C	248 Liters	<input type="checkbox"/> H	6910 Liters
<input type="checkbox"/> D	415 Liters	<input type="checkbox"/> Other	_____ Liters

Liters Other Liters

OXYGEN			
oxygen gas			
Product Information			
Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:58632-001
Route of Administration	RESPIRATORY (INHALATION)		
Active Ingredient/Active Moiety			
Ingredient Name		Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)		OXYGEN	990 mL in 1 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:58632-001-01	7952 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
2	NDC:58632-001-02	170 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
3	NDC:58632-001-03	618 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
4	NDC:58632-001-04	415 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
5	NDC:58632-001-05	2264 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
6	NDC:58632-001-06	3537 L in 1 CYLINDER; Type 0: Not a Combination Product	07/01/2005	
7	NDC:58632-001-07	5468 L in 1 DEWAR; Type 0: Not a Combination Product	07/01/2005	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205712	07/01/2005	

Labeler - GIBBS WELDING SUPPLY, INC. (621442615)

Establishment

Name	Address	ID/FEI	Business Operations
GIBBS WELDING SUPPLY, INC.		621442615	manufacture(58632-001)

Revised: 10/2023

GIBBS WELDING SUPPLY, INC.