

**AIR- air gas**  
**American Welding & Gas, Inc.**

-----  
**Air**

AIR, COMPRESSED

UN1002

MEDICAL AIR, USP

WARNING: For breathing support when used by properly trained personnel. For medical applications, Rx only. Administration of Medical Air may be hazardous or contraindicated. For use only by or under the supervision of licensed practitioner who is experienced in the use and administration of Medical Air and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

WARNING: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. SUPPORTS COMBUSTION. Do not handle until all safety precautions have been read and understood. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use. CAS 132259-10-0

CONTENTS

Cylinder Type H M 40 E Cu. Ft. 214 108 38 23 Liters 6,145 3,058 1,076 651  
SCOTT-GROSS COMPANY, INC.

664 MAGNOLIA AVENUE

LEXINGTON, KY 40505

1-800-967-6874

WWW.SCOTTGROSS.COM

DO NOT REMOVE THIS PRODUCT LABEL

**AIR,  
COMPRESSED**

**UN1002**



**SCOTT-GROSS COMPANY, INC.**  
664 MAGNOLIA AVENUE  
LEXINGTON, KY 40505  
1-800-967-6874  
WWW.SCOTTGROSS.COM

**MEDICAL AIR, USP**

**WARNING:** For breathing support when used by properly trained personnel. For medical applications, Rx only. Administration of Medical Air may be hazardous or contraindicated. For use only by or under the supervision of a licensed practitioner who is experienced in the use and administration of Medical Air and is familiar with the indications, effects, dosages, methods, and frequency and duration of administration, and with the hazards, contraindications and side effects, and the precautions to be taken.

**WARNING:** CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. SUPPORTS COMBUSTION. Do not handle until all safety precautions have been read and understood. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 °C (125 °F). Read and follow the Safety Data Sheet (SDS) before use.  
CAS 132259-10-0

**CONTENTS**

Cylinder Type	Cu. Ft.	Liters
<input type="checkbox"/> H	217	6,145
<input type="checkbox"/> M	108	3,058
<input type="checkbox"/> 40	38	1,076
<input type="checkbox"/> E	23	651
<input type="checkbox"/> _____	_____	_____

DO NOT REMOVE THIS LABEL.

SG 236 V002

**AIR**

air gas

**Product Information**

<b>Product Type</b>	HUMAN PRESCRIPTION DRUG	<b>Item Code (Source)</b>	NDC:44076-020
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

**Active Ingredient/Active Moiety**

Ingredient Name	Basis of Strength	Strength
<b>AIR</b> (UNII: K21NZZ5Y0B) (AIR - UNII:K21NZZ5Y0B)	AIR	1000 mL in 1 L

**Packaging**

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:44076-020-01	6145 L in 1 CYLINDER; Type 0: Not a Combination Product	11/01/2006	
2	NDC:44076-020-02	3058 L in 1 CYLINDER; Type 0: Not a Combination Product	11/01/2006	
3	NDC:44076-020-03	1076 L in 1 CYLINDER; Type 0: Not a Combination Product	11/01/2006	
4	NDC:44076-020-04	651 L in 1 CYLINDER; Type 0: Not a Combination Product	11/01/2006	

**Marketing Information**

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date

NDA	NDA205821	11/01/2006	
-----	-----------	------------	--

**Labeler** - American Welding & Gas, Inc. (068181965)

### **Establishment**

<b>Name</b>	<b>Address</b>	<b>ID/FEI</b>	<b>Business Operations</b>
AMERICAN WELDING & GAS, INC.		116724243	manufacture(44076-020)

Revised: 10/2023

American Welding & Gas, Inc.