

OXYGEN- oxygen gas
Airweld, Inc.

Oxygen

OXYGEN COMPRESSED LABEL

OXYGEN, COMPRESSED USP UN 1072 OXYGEN 2 (R-K14) 115856

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. **Produced by Air Liquefaction.** **DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 **DO NOT REMOVE THIS PRODUCT LABEL.**

Rev: 3/15



Oxygen Liquid

OXYGEN, REFRIGERATED LIQUID USP UN1073

OXYGEN 2 (R-K14) 115859

! ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.!

DO NOT CHANGE OR FORCE FIT CONNECTINS.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**.

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction of resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin, or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52°C (125°F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the **Material Safety Data Sheet (MSDS)**.

FIRST AID FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

Rev: 3/15

**OXYGEN,
REFRIGERATED LIQUID
USP**

UN 1073

**OXYGEN
2**

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION

WARNING:
For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. Keep out of reach of children; and Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act. **DANGER: MAY CAUSE OR INTENSIFY FIRE: OXIDIZER. CONTAINS REFRIGERATED GAS: MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.**

Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. **DO NOT** change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Read and follow the Safety Data Sheet (SDS) before use. **FIRST AID: IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. **KEEP OUT OF REACH OF CHILDREN.** User shall secure cylinders in use and in storage.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

Rev: 3/15

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:64650-345
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:64650-345-10	400 L in 1 CAN; Type 0: Not a Combination Product	01/01/1971	
2	NDC:64650-345-11	650 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1971	
3	NDC:64650-345-12	3540 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1971	
4	NDC:64650-345-13	123135 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1971	
5	NDC:64650-345-14	123135 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1971	
6	NDC:64650-345-15	98 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1971	
7	NDC:64650-345-16	141 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1971	
8	NDC:64650-345-17	234 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1971	
9	NDC:64650-345-18	1554 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1971	
10	NDC:64650-345-19	3160 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1971	
11	NDC:64650-345-20	6270 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1971	
12	NDC:64650-345-21	8150 L in 1 CYLINDER; Type 0: Not a Combination Product	01/01/1971	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	01/01/1971	

Labeler - Airweld, Inc. (111837006)

Registrant - Airweld, Inc. (111837006)

Establishment

Name	Address	ID/FEI	Business Operations
Airweld, Inc.		111837006	manufacture(64650-345)

Revised: 10/2023

Airweld, Inc.