

OXYGEN- oxygen gas
Capitol Welders Supply Co., Inc.

OXYGEN COMPRESSED USP 001

OXYGEN COMPRESSED USP PRODUCT LABEL

OXYGEN COMPRESSED USP OXYGEN 2

UN1072

PRODUCED BY AIR LIQUEFACTION

17033 (12/14)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. **DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE. MAY EXPLODE IF HEATED.** Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when the ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.

CAS 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

CWI FILLED & DISTRIBUTED BY: CAPITAL WELDERS SUPPLY CO.

5111 CHOCTAW DRIVE • BATON ROUGE, LA 70805

(225) 383-3717

CONTENTS: LTRS.
_____ CU. FT.

OXYGEN, COMPRESSED USP
UN1072
PRODUCED BY AIR LIQUEFACTION

OXYGEN 2

CWI FILLED & DISTRIBUTED BY: CAPITAL WELDERS SUPPLY CO.
5111 CHOCTAW DRIVE • BATON ROUGE, LA 70805
(225) 383-3717

CAS 7782-44-7

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. **DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS GAS UNDER PRESSURE. MAY EXPLODE IF HEATED.** Do not handle until all safety precautions have been read and understood. Keep and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125°F). Read and follow the Safety Data Sheet (SDS) before use.

DO NOT REMOVE THIS PRODUCT LABEL

CONTENTS: LTRS.
_____ CU. FT.

Liquid Oxygen Tag

Linde LIQUID OXYGEN, U.S.P. DELIVERY TAG

FILLED AND DISTRIBUTED BY:

THIS VESSEL CONTAINS OXYGEN, U.S.P. (See reverse side for test results) OXYGEN PRODUCED BY THE AIR LIQUEFACTION PROCESS

LOT NUMBER _____ SERIAL NUMBER _____ AMOUNT _____ INS., LBS., GALS., LITERS, CU. FT.

USP TESTS

TEST ID ODOR ASSAY FOR CUSTOMER USE TO DOCUMENT TESTS PERFORMED ON THIS

LIMITS OK NONE GREATER THAN LESS THAN 99.2 % VESSEL RESULT

METHOD OF ANALYSIS FOR ASSAY IS THE PARAMAGNETIC OXYGEN ANALYZER

MANUFACTURE _____ MODEL _____ CUSTOMER WITNESSED TEST: __ YES __ NO

SUPPLIER'S SIGNATURE _____ DATE _____ CUSTOMER'S SIGNATURE _____ DATE _____

Linde

LIQUID OXYGEN, U.S.P. DELIVERY TAG

FILLED AND DISTRIBUTED BY:

THIS VESSEL CONTAINS OXYGEN, U.S.P. (See reverse side for test results)
OXYGEN PRODUCED BY THE AIR LIQUEFACTION PROCESS

LOT NUMBER _____ SERIAL NUMBER _____
AMOUNT _____ INS., LBS., GALS., LITERS, CU. FT.

USP TESTS			
TEST	ID	ODOR	ASSAY
LIMITS	OK	NONE	≥ 99.2%
RESULT			

FOR CUSTOMER USE TO DOCUMENT TESTS PERFORMED ON THIS VESSEL	

METHOD OF ANALYSIS FOR ASSAY IS THE PARAMAGNETIC OXYGEN ANALYZER

MANUFACTURER _____ MODEL _____

CUSTOMER WITNESSED TESTS: YES NO

SUPPLIER'S SIGNATURE _____ DATE _____

CUSTOMER'S SIGNATURE _____ DATE _____



LIQUID OXYGEN, U.S.P. DELIVERY TAG

FILLED AND DISTRIBUTED BY:

THIS VESSEL CONTAINS OXYGEN, U.S.P. (See reverse side for test results)
OXYGEN PRODUCED BY THE AIR LIQUEFACTION PROCESS

LOT NUMBER _____ SERIAL NUMBER _____
AMOUNT _____ INS., LBS., GALS., LITERS, CU. FT.

USP TESTS			
TEST	ID	ODOR	ASSAY
LIMITS	OK	NONE	≥ 99.2%
RESULT			

FOR CUSTOMER USE TO DOCUMENT TESTS PERFORMED ON THIS VESSEL

METHOD OF ANALYSIS FOR ASSAY IS THE PARAMAGNETIC OXYGEN ANALYZER

MANUFACTURER _____ MODEL _____

CUSTOMER WITNESSED TESTS: YES NO

SUPPLIER'S SIGNATURE _____ DATE _____

CUSTOMER'S SIGNATURE _____ DATE _____

Oxygen Refrigerated Liquid Label

OXYGEN REFRIGERATED LIQUID USP UN1073 OXYGEN 2

LOT #: _____ CONTENTS _____ LITERS _____

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION.

WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

KEEP OIL, GREASE AND COMBUSTIBLES AWAY. USE ONLY WITH EQUIPMENT CLEANED FOR OXYGEN SERVICE. STORE AND USE WITH ADEQUATE VENTILATION. DO NOT GET LIQUID IN EYES, ON SKIN OR CLOTHING. FOR LIQUID WITHDRAWAL, WEAR FACE SHIELD AND GLOVES. DO NOT DROP. USE HAND TRUCK FOR CONTAINER MOVEMENT. AVOID SPILLS. DO NOT WALK OR ROLL EQUIPMENT OVER SPILLS. CLOSE VALVE AFTER EACH USE AND WHEN EMPTY. USE IN ACCORDANCE WITH THE MATERIAL SAFETY DATA SHEET (MSDS)

FIRST AID: IN CASE OF FROSTBITE OBTAIN MEDICAL TREATMENT IMMEDIATELY.

WARNING: FOR EMERGENCY USE ONLY WHEN ADMINISTERED BY PROPERLY TRAINED PERSONNEL FOR OXYGEN DEFICIENCY AND RESUSCITATION. FOR ALL OTHER MEDICAL APPLICATIONS, CAUTION: FEDERAL LAW PROHIBITS DISPENSING WITHOUT

PRESCRIPTION.

UNINTERRUPTED USE OF HIGH CONCENTRATIONS OF OXYGEN OVER A LONG DURATION WITHOUT MONITORING ITS EFFECT ON OXYGEN CONTENT OF ARTERIAL BLOOD MAY BE HARMFUL. USE ONLY WITH PRESSURE REDUCING EQUIPMENT AND APPARATUS DESIGNED FOR OXYGEN. DO NOT ATTEMPT TO USE ON PATIENTS WHO HAVE STOPPED BREATHING, UNLESS USED IN CONJUNCTION WITH RESUSCITATIVE EQUIPMENT.

PRODUCED BY AIR LIQUEFACTION. DO NOT REMOVE THIS PRODUCT LABEL.

FILLED AND DISTRIBUTED BY: CAPITOL WELDERS SUPPLY CO. 1101 CHOCTAW DRIVE BATON ROUGH, LA 70805 (504) 383-3717 45136 REV:1/98

OXYGEN, REFRIGERATED LIQUID

**USP
UN1073**



LOT #: _____

CONTENTS: _____ LITERS

↑ ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. ↑

WARNING: EXTREMELY COLD OXIDIZING LIQUID AND GAS UNDER PRESSURE.
VIGOROUSLY ACCELERATES COMBUSTION.
COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT.
CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away.
Use only with equipment cleaned for oxygen service.
Store and use with adequate ventilation.
Do not get liquid in eyes, on skin or clothing.
Protect with hand, wear face shield and gloves.

For liquid withdrawal, wear face shield and gloves.
Do not drop. Use hand truck for container movement.
Avoid spills. Do not walk on or roll equipment over spills.
Close valve after each use and when empty.
Use in accordance with the Material Safety Data Sheet (MSDS).

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately.

WARNING! For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Caution: Federal law prohibits dispensing without prescription.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction

DO NOT REMOVE THIS PRODUCT LABEL.

Filled and Distributed by:
Capitol Welders Supply Co.
1101 Choctaw Drive • Baton Rouge, LA 70805
(504) 383-3717

45136
REV. 1/98

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:49571-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L

Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:49571-001-01	170 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
2	NDC:49571-001-02	196 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
3	NDC:49571-001-03	248 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
4	NDC:49571-001-04	630 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
5	NDC:49571-001-05	1738 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
6	NDC:49571-001-06	103 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
7	NDC:49571-001-07	150 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
8	NDC:49571-001-08	255 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
9	NDC:49571-001-09	426 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
10	NDC:49571-001-10	680 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
11	NDC:49571-001-11	682 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
12	NDC:49571-001-12	6900 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
13	NDC:49571-001-13	9310 L in 1 CYLINDER; Type 0: Not a Combination Product	12/23/2017	
14	NDC:49571-001-14	1376888 L in 1 DEWAR; Type 0: Not a Combination Product	12/23/2017	
15	NDC:49571-001-15	137688 L in 1 DEWAR; Type 0: Not a Combination Product	12/23/2017	
16	NDC:49571-001-16	154800 L in 1 DEWAR; Type 0: Not a Combination Product	12/23/2017	
17	NDC:49571-001-17	172000 L in 1 DEWAR; Type 0: Not a Combination Product	12/23/2017	
18	NDC:49571-001-18	197800 L in 1 DEWAR; Type 0: Not a Combination Product	12/23/2017	
19	NDC:49571-001-19	227900 L in 1 DEWAR; Type 0: Not a Combination Product	12/23/2017	
20	NDC:49571-001-20	290563 L in 1 TANK; Type 0: Not a Combination Product	12/23/2017	
21	NDC:49571-001-21	618485 L in 1 TANK; Type 0: Not a Combination Product	12/23/2017	
22	NDC:49571-001-22	325518 L in 1 TANK; Type 0: Not a Combination Product	12/23/2017	

Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NDA	NDA205767	01/01/1959	

Labeler - Capitol Welders Supply Co., Inc. (003851466)**Registrant** - Capitol Welders Supply Co., Inc. (003851466)

Establishment

Name	Address	ID/FEI	Business Operations
Capitol Welders Supply Co., Inc.		003851466	manufacture(49571-001)

Revised: 10/2018

Capitol Welders Supply Co., Inc.