OXYGEN- oxygen gas Corrigan Propane LLC dba Blue Water Industrial Products

OXYGEN COMPRESSED LABEL

OXYGEN, COMPRESSED USP UN 1072 OXYGEN 2 17033 (12/14)

PRODUCED BY AIR LIQUEFACTION

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. **DANGER:** MAY CAUSE OR INTENSIFY FIRE: OXIDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52°C (125° F). Read and follow the Safety Data Sheet (SDS) before use. CAS 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

CONTLINIS.
LTRS:
CU.FT.

CONTENTS:

BLUEWATER INDUSTRIAL PRODUCTS INC.

37280 GREEN ST • NEW BALTIMORE, MI 48047

(586) 725-6300





Refrigerated Liquid Oxygen Label
OXYGEN, REFRIERATED LIQUID USP UN1073
Rx ONLY
Rx ONLY.

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction of resuscitative equipment. **Produced by Air Liquefaction.**

DANGER: MAY CAUSE OR INTENSIFY FIRE; OXIDER, CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBELS IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only the equipment of compatible materials equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. **FIRST AID FIRST AID: IF ON SKIN**: Thaw affected parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL

BLUEWATER INDUSTRIAL PRODUCTS INC.

37280 GREEN ST • NEW BALTIMORE, MI 48047

(586) 725-6300

41550 (12/14)

OXYGEN, REFRIGERATED LIQUID USP UN1073



WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **R**, only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction.

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for

oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. FIRST AID: IF ON SKIN: thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

BLUEWATER INDUSTRIAL PRODUCTS, INC.

37280 GREEN ST • NEW BALTIMORE, MI 48047 (586) 725-6300

41550 (12/14)

OXYGEN, REFRIGERATED LIQUID USP UN1073



WARNING:

For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **R**, only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.

Produced by Air Liquefaction.

DANGER:

MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for

oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use. FIRST AID: IF ON SKIN: thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

BLUEWATER INDUSTRIAL PRODUCTS, INC.

37280 GREEN ST • NEW BALTIMORE, MI 48047 (586) 725-6300

41550 (12/14)

OXYGEN

oxygen gas

Product Information				
Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:44517-001	
Route of Administration	RESPIRATORY (INHALATION)			

Active Ingredient/Active Moiety			
Ingredient Name	Basis of Strength	Strength	
OXYGEN (UNII: S88TT14065) (OXYGEN - UNII:S88TT14065)	OXYGEN	99 L in 100 L	

Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:44517- 001-01	9310 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2008	
2	NDC:44517- 001-02	6900 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2008	
3	NDC:44517- 001-03	4250 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2008	
4	NDC:44517- 001-04	3500 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2008	
5	NDC:44517- 001-05	2320 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2008	
6	NDC:44517- 001-06	1970 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2008	
7	NDC:44517- 001-07	625 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2008	
8	NDC:44517- 001-08	360 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2008	
9	NDC:44517- 001-09	570 L in 1 CYLINDER; Type 0: Not a Combination Product	12/01/2008	
10	NDC:44517- 001-10	127100 L in 1 DEWAR; Type 0: Not a Combination Product	12/01/2008	
11	NDC:44517- 001-11	141500 L in 1 DEWAR; Type 0: Not a Combination Product	12/01/2008	

Marketing Information				
Marketing Application Number or Monograph Category Citation		Marketing Start Date	Marketing End Date	
NDA	NDA205889	12/01/2008		

Labeler - Corrigan Propane LLC dba Blue Water Industrial Products (105410989)

Registrant - Corrigan Propane LLC dba Blue Water Industrial Products (117163181)

Establishment				
Name	Address	ID/FEI	Business Operations	
Corrigan Propane LLC dba Blue Water Industrial Products		117163181	manufacture(44517-001)	

Establishment				
Name	Address	ID/FEI	Business Operations	
Matheson Tri-Gas, Inc.		099963340	manufacture(44517-001)	

Revised: 10/2023 Corrigan Propane LLC dba Blue Water Industrial Products