

**OXYGEN- oxygen gas**  
**Depke Welding Supplies, Inc.**

-----  
**Oxygen**

OXYGEN, COMPRESSED USP UN1072 OXYGEN 2

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act.

**DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.** Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. Open valve slowly. Close valve after each use and when empty. Protect from sunlight when ambient temperature exceeds 52 C (125 F). Read and follow the Safety Data Sheet (SDS) before use.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL

CONTENTS: T-323 CF K-238CF E, M-118 CF Q-81 CF M60-57 CF E Pur-23 CF DD-22 CF D Pur-14 CF M9-8.5 CF M6-5.7 CF

Depke GASES AND WELDING SUPPLIES 628 E WILLIAMS ST DANVILLE, IL 61832 1-800-38-DEPKE



REFRIGERATED LIQUID OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2

CONTENTS: LTRS: CU FT:

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx only. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. Produced by Air Liquefaction.

**DANGER: MAY CAUSE OR INTENSIFY FIRE; OXYDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID**

OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire; Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills, Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

FIRST AID: IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

CAS: 7782-44-7 DO NOT REMOVE THIS PRODUCT LABEL.

Depke GASES AND WELDING SUPPLIES 628 E WILLIAMS ST DANVILLE, IL 61832 1-800-38-DEPKE

# REFRIGERATED LIQUID

**OXYGEN,  
REFRIGERATED  
LIQUID  
USP**

**UN1073**



CONTENTS: \_\_\_\_\_

LTRS:

CU FT:

**WARNING:** For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, **Rx only**. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Keep out of reach of children. Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the *Federal Food, Drug, and Cosmetic Act*.

**Produced by Air Liquefaction.**

**DANGER:** MAY CAUSE OR INTENSIFY FIRE; OXIDIZER. CONTAINS REFRIGERATED GAS; MAY CAUSE CRYOGENIC BURNS OR INJURY. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. Do not handle until all safety precautions have been read and understood. Keep and store away from clothing and other combustible materials. Keep valves and fittings free from grease and oil. Use and store only outdoors or in a well-ventilated place. Wear cold insulating gloves, face shield, and eye protection. In case of fire: Stop leak if safe to do so. Use a back flow preventive device in the piping. Use only with equipment of compatible materials

of construction and rated for cylinder pressure. Use only with equipment cleaned for oxygen service. DO NOT change or force fit connections. Avoid spills. Do not walk on or roll equipment over spills. Close valve after each use and when empty. Always keep container in upright position. Read and follow the Safety Data Sheet (SDS) before use.

**FIRST AID: IF ON SKIN:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.  
CAS: 7782-44-7



**DO NOT REMOVE THIS PRODUCT LABEL**

**Depke** 628 E WILLIAMS ST  
DANVILLE, IL 61832  
GASES AND WELDING SUPPLIES 1-800-38-DEPKE 47136  
(01/15)

## OXYGEN

oxygen gas

### Product Information

<b>Product Type</b>	PRESCRIPTION ANIMAL DRUG	<b>Item Code (Source)</b>	NDC:10690-011
<b>Route of Administration</b>	RESPIRATORY (INHALATION)		

### Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	995 mL in 1 L

### Packaging

#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:10690-011-01	163 L in 1 CYLINDER		
2	NDC:10690-011-02	236 L in 1 CYLINDER		
3	NDC:10690-011-03	396.43 L in 1 CYLINDER		
4	NDC:10690-011-04	651.28 L in 1 CYLINDER		
5	NDC:10690-011-05	1699.01 L in 1 CYLINDER		
6	NDC:10690-011-06	3341.3 L in 1 CYLINDER		
7	NDC:10690-011-07	6739.34 L in 1 CYLINDER		
8	NDC:10690-011-08	9344.5 L in 1 CYLINDER		
9	NDC:10690-011-09	127425.8 L in 1 DEWAR		
10	NDC:10690-011-10	162963.452 L in 1 DEWAR		
11	NDC:10690-011-11	235926.905 L in 1 DEWAR		
12	NDC:10690-011-12	387855.849 L in 1 DEWAR		
13	NDC:10690-011-13	621413.201 L in 1 DEWAR		
14	NDC:10690-011-14	945188.026 L in 1 DEWAR		
15	NDC:10690-011-15	160 L in 1 CYLINDER		

16 | NDC:10690-011-16 | 200 L in 1 CYLINDER

## Marketing Information

Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
NADA	NADA141396	01/01/1978	

**Labeler** - Depke Welding Supplies, Inc. (025382276)

## Establishment

Name	Address	ID/FEI	Business Operations
Depke Welding Supplies, Inc		025382276	manufacture

## Establishment

Name	Address	ID/FEI	Business Operations
Depke Welding Supplies, Inc		041939869	manufacture

## Establishment

Name	Address	ID/FEI	Business Operations
Depke Welding Supplies, Inc		025565821	manufacture

Revised: 2/2016

Depke Welding Supplies, Inc.