

OXYGEN - oxygen gas
Encompass Medical & Specialty Gases, Ltd.

Disclaimer: This drug has not been found by FDA to be safe and effective, and this labeling has not been approved by FDA. For further information about unapproved drugs, click here.

Oxygen Label

OXYGEN, Compressed USP UN1072 OXYGEN 2 16639 (R 08/10)

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx ONLY. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for use with oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction. WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Keep oil and grease away. Open valve slowly. Store and use with adequate ventilation. Use only with equipment cleaned for Oxygen service and rated for cylinder pressure. Use a back flow preventive device in the piping. Close valve after each use and when empty. Cylinder temperature should not exceed 52 C (125F). Use in accordance with Material Safety Data Sheet (MSDS).

CAS: 7782-44-7 RETURN WITH 25 PSIG

DO NOT REMOVE THIS PRODUCT LABEL.

Cylinders must be refilled by:

Encompass Medical and Specialty Gases, LTD. 4646 Linden Road P.O. Box 5404 Rockford, IL 61109

CONTENTS: 690 LTRS CYL. SIZE E TOP PSIG at 70 F 2015



REFRIGERATED LIQUID

OXYGEN, REFRIGERATED LIQUID USP UN1073 OXYGEN 2

ALWAYS KEEP CONTAINER IN UPRIGHT POSITION. DO NOT CHANGE OR FORCE FIT CONNECTIONS.

CONTENTS: LTRS. CU. FT.

WARNING: For emergency use only when administered by properly trained personnel for oxygen

deficiency and resuscitation. For all other medical applications, Rx ONLY. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for use with oxygen. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment. Produced by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE . VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT. CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease and combustibles away. Use only with equipment cleaned for oxygen. Store and use with adequate ventilation. Do not get liquid in eyes, on skin, or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52 C (125F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with Material Safety Data Sheet (MSDS). **FIRST AID : IN CASE OF FROSTBITE**, obtain medical treatment immediately.

CAS: 7782-44-7

DO NOT REMOVE THIS PRODUCT LABEL.

Cylinders must be refilled by:

Encompass Medical and Specialty Gases, LTD. 4646 Linden Road P.O. Box 5404 Rockford, IL 61109 47136 (R 10/05)



CONTENTS:

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation, for all other medical applications, **Rx only.**

Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Use only with pressure reducing equipment and apparatus designed for oxygen. Do not attempt to use on patients who have stopped breathing, unless used in conjunction with resuscitative equipment.

Produced by Air Liquefaction.

WARNING: EXTREMELY COLD, OXIDIZING LIQUID AND GAS UNDER PRESSURE. VIGOROUSLY ACCELERATES COMBUSTION. COMBUSTIBLES IN CONTACT WITH LIQUID OXYGEN MAY EXPLODE ON IGNITION OR IMPACT CAN CAUSE SEVERE FROSTBITE.

Keep oil, grease, and combustibles away. Use only with equipment cleaned for oxygen service. Store and use with adequate ventilation. Do not get liquid in eyes, on skin, or clothing. For liquid withdrawal, wear face shield and gloves. Do not drop. Use suitable hand truck for container movement. Avoid spills. Do not walk on or roll equipment over spills. Cylinder temperature should not exceed 52°C (125°F). Close valve after each use and when empty. Use a back flow preventive device in the piping. Use in accordance with the **Material Safety Data Sheet (MSDS)**.

FIRST AID: IN CASE OF FROSTBITE, obtain medical treatment immediately. CAS: 7782-44-7 **DO NOT REMOVE THIS PRODUCT LABEL.**

Cylinders must be refilled by:
Encompass Medical & Specialty Gases, LTD.
4646 Linden Road • P.O. Box 5404 • Rockford, IL 61109

47136
(R 10/05)

Produced by air liquefaction

OXYGEN, Compressed U.S.P. UN1072 OXYGEN 2

WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications, Rx ONLY. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

WARNING: HIGH PRESSURE OXIDIZING GAS. VIGOROUSLY ACCELERATES COMBUSTION. Use only with pressure reducing equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure. Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects, free of oil and grease to avoid violent ignition. Federal law requires that this container be refilled with oxygen USP only by establishments registered

as a drug manufacturer in accordance with the Federal Food, Drug and Cosmetic Act. Pursuant to recommendations by the Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 125F. DO NOT REMOVE THIS PRODUCT LABEL.

Use a back flow preventive device in the piping. Use only in accordance with product instructions and Material Safety Data Sheet.

Cylinders must be refilled by:

Encompass Medical and Specialty Gases, LTD. 4646 Linden Road P.O. Box 5404 Rockford, IL 61109

CAS: 7782-44-7 RETURN WITH 25 PSIG

DO NOT REMOVE THIS PRODUCT LABEL

Cylinder contents at 70F

Cylinder size

Size E 690 liters 2015 PSIG

Size D 420 Liters 2015 PSIG

Size M6 164 Liters 2015 PSIG

STORE AND USE WITH ADEQUATE VENTILATION

Date: 0810 Label:0035-647



WARNING: For emergency use only when administered by properly trained personnel for oxygen deficiency and resuscitation. For all other medical applications: Rx ONLY. Uninterrupted use of high concentrations of oxygen over a long duration, without monitoring its effect on oxygen content of arterial blood, may be harmful. Do not attempt to use on patients who have stopped breathing unless used in conjunction with resuscitative equipment.

**WARNING: HIGH PRESSURE OXIDIZING GAS
VIGOROUSLY ACCELERATES COMBUSTION**

- Use only with pressure reducing equipment and apparatus cleaned and designed for oxygen service and rated for cylinder pressure.
- Open valve slowly. Close valve after each use and when empty. Keep cylinder, cylinder valve, all equipment that connects, free of oil and grease to avoid violent ignition.
- Federal law requires that this container be refilled with oxygen USP only by establishments registered as a drug manufacturer in accordance with the Federal Food, Drug, and Cosmetic Act.
- Pursuant to recommendations by Compressed Gas Association, do not expose pressurized cylinders to temperatures in excess of 125°F.
- DO NOT REMOVE THIS PRODUCT LABEL.
Use a back flow preventive device in the piping.
Use only in accordance with product instructions and material safety data sheet.

Cylinders must be refilled by:

Encompass Medical & Specialty Gases, Ltd

4646 Linden Rd, PO Box 5404
Rockford IL 61109

CAS: 7782-44-7 RETURN WITH 25 PSIG
DO NOT REMOVE THIS PRODUCT LABEL

Cylinder contents at 70° F

Cylinder size

- Size E 690 Liters 2015 PSIG
- Size D 420 Liters 2015 PSIG
- Size M6 164 Liters 2216 PSIG

STORE AND USE WITH
ADEQUATE VENTILATION

Date: 0810 Label: 0035-647

OXYGEN

oxygen gas

Product Information

Product Type	HUMAN PRESCRIPTION DRUG	Item Code (Source)	NDC:48883-001
Route of Administration	RESPIRATORY (INHALATION)		

Active Ingredient/Active Moiety

Ingredient Name	Basis of Strength	Strength
Oxygen (UNII: S88TT14065) (Oxygen - UNII:S88TT14065)	Oxygen	990 mL in 1 L

Packaging				
#	Item Code	Package Description	Marketing Start Date	Marketing End Date
1	NDC:48883-001-01	113 L in 1 CYLINDER		
2	NDC:48883-001-02	165 L in 1 CYLINDER		
3	NDC:48883-001-03	171 L in 1 CYLINDER		
4	NDC:48883-001-04	248 L in 1 CYLINDER		
5	NDC:48883-001-05	420 L in 1 CYLINDER		
6	NDC:48883-001-06	647 L in 1 CYLINDER		
7	NDC:48883-001-07	690 L in 1 CYLINDER		
8	NDC:48883-001-08	1699 L in 1 CYLINDER		
9	NDC:48883-001-09	1846 L in 1 CYLINDER		
10	NDC:48883-001-10	2497 L in 1 CYLINDER		
11	NDC:48883-001-11	3511 L in 1 CYLINDER		
12	NDC:48883-001-12	3470 L in 1 CYLINDER		
13	NDC:48883-001-13	4361 L in 1 CYLINDER		
14	NDC:48883-001-14	6900 L in 1 CYLINDER		
15	NDC:48883-001-15	9340 L in 1 CYLINDER		
16	NDC:48883-001-16	127427 L in 1 CYLINDER		
17	NDC:48883-001-17	64308 L in 1 CYLINDER		

Marketing Information			
Marketing Category	Application Number or Monograph Citation	Marketing Start Date	Marketing End Date
unapproved medical gas		01/01/1955	

Labeler - Encompass Medical & Specialty Gases, Ltd. (963344143)

Establishment

Name	Address	ID/FEI	Business Operations
Encompass Medical & Specialty Gases, Ltd.		963344143	manufacture

Establishment

Name	Address	ID/FEI	Business Operations
Encompass Medical & Specialty Gases, Ltd.		963719286	manufacture

Establishment

Name	Address	ID/FEI	Business Operations
Encompass Medical & Specialty Gases, Ltd.		963719096	manufacture

Establishment

Name	Address	ID/FEI	Business Operations
Encompass Medical & Specialty Gases, Ltd.		963718361	manufacture